

RT255R0HIRX2



Article Number: 115-01300

Releasable Cable Tie, 20" Long, 250 lb Tensile Strength, PA66HIRHSUV, Black, 25/pkg



Base Data

Local Order Number RT255R0HIRX2

Type RT255R

Color Black (BK)

Features and Benefits

- High impact, heat and UV stabilized releasable cable ties contain an impact modifier allowing greater flexibility and greater resistance to vibration.
- Special design offers a release feature for quick and easy access to wire bundles.
- Head design provides high tensile strength with very low insertion force even after repeated use.

Product Description HellermannTyton releasable cable ties offer a release feature in the head allowing for easy access to wire bundles when changes are necessary. The head design guarantees high tensile strength even after repeated use, as well as a low insertion force. For high volume applications, tensioning tools are available to ensure consistent and safe installation.

Fixation Method (FF) None

Identification Plate Position none

Releasable Closure (Yes/No) Yes

Short Description Releasable Cable Tie, 20" Long, 250 lb Tensile Strength, PA66HIRHSUV, Black, 25/pkg

Product Dimensions

Minimum Tensile Strength (imperial) 250.0 lbs

Minimum Tensile Strength (N) 1115.0 N

Length L (imperial) 20.0 "

Length L (metric) 508.0 mm

Width W (imperial) 0.5 "

Width W (metric) 12.6 mm

Cable Tie Width Max (imperial) 0.49 "

Cable Tie Width max. (metric) 12.5 mm

Bundle Diameter min (imperial) 0.49 "

Bundle Diameter min (metric) 12.5 mm

Bundle Diameter max (imperial) 5.0 "

Bundle Diameter max (metric) 127.0 mm

Logistics and Packaging

Quantity per bag

Package Quantity 25

Carton Quantity 500

Material and Specifications

Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	PA66HIRHSUV
Flammability	UL94 HB
Operating Temperature	-40 °F to +230 °F (-40 °C to +110 °C)
ROHS Conformity	Yes
Certification / Specification	UL
UL Listed (US and Canada)	No
UL Recognized (US and Canada)	Yes