# HellermannTyton

## **RT40R9M4**

Article Number: 115-06204

Releasable Cable Tie, 8.5" Long, 40 lb Tensile Strength, PA66, Natural, 1000/pkg



RoHS

#### Base Data

Local Order Number	RT40R9M4
Туре	RT40R
Color	Natural (NA)
Features and Benefits	<ul> <li>Special design offers a release feature for quick and easy access to wire bundles.</li> <li>Head design provides high tensile strength with very low insertion force even after repeated use.</li> <li>Bent tail ensures a quick and simple installation.</li> </ul>
Product Description	HellermannTyton releasable cable ties offer a release feature in the head allowing for easy access to wire bundles when changes are necessary. The head design guarantees high tensile strength even after repeated use, as well as a low insertion force. For high volume applications, tensioning tools are available to ensure consistent and safe installation.
Fixation Method (FF)	None
Identification Plate Position	none
Releasable Closure (Yes/No)	Yes
Tie Closure	plastic pawl
Variant	Inside Serrated
Short Description	Releasable Cable Tie, 8.5" Long, 40 lb Tensile Strength, PA66, Natural, 1000/pkg

#### **Product Dimensions**

Minimum Tensile Strength (imperial)	40.0 lbs
Minimum Tensile Strength (N)	180.0 N
Length L (imperial)	8.5 "
Length L (metric)	215.0 mm
Width W (imperial)	0.16 "
Width W (metric)	4.0 mm
Bundle Diameter min (imperial)	0.06 "
Bundle Diameter min (metric)	1.5 mm
Bundle Diameter max (imperial)	2.0 "
Bundle Diameter max (metric)	51.0 mm

### Logistics and Packaging

Quantity per	bag
Package Quantity	1000
Carton Quantity	5000
Weight (Metric)	1.2 kg

Material	Polyamide 6.6 (PA66)
Material Shortcut	PA66
CSA Certified	No
Flammability	UL94 V2
Operating Temperature	-40 °F to +185 °F (-40 °C to +85 °C)
ROHS Conformity	Yes
Certification / Specification	UL
UL Listed (US and Canada)	No
UL Recognized (US and Canada)	Yes

© HellermannTyton 2014