

## RT50S9C2

Article Number: 115-06319

Releasable Cable Tie, 6.3" Long, 50 lb Tensile Strength, PA66, Natural, 100/pkg



### Base Data

Local Order Number RT50S9C2

Type RT50S

Color Natural (NA)

- Features and Benefits**
- Special design offers a release feature for quick and easy access to wire bundles.
  - Head design provides high tensile strength with very low insertion force even after repeated use.
  - Bent tail ensures a quick and simple installation.

**Product Description** HellermannTyton releasable cable ties offer a release feature in the head allowing for easy access to wire bundles when changes are necessary. The head design guarantees high tensile strength even after repeated use, as well as a low insertion force. For high volume applications, tensioning tools are available to ensure consistent and safe installation.

Fixation Method (FF) None

Identification Plate Position none

Releasable Closure (Yes/No) Yes

Tie Closure plastic pawl

Variant Inside Serrated

Short Description Releasable Cable Tie, 6.3" Long, 50 lb Tensile Strength, PA66, Natural, 100/pkg

### Product Dimensions

Minimum Tensile Strength (imperial) 50.0 lbs

Minimum Tensile Strength (N) 225.0 N

Length L (imperial) 6.3 "

Length L (metric) 160.0 mm

Width W (imperial) 0.18 "

Width W (metric) 4.6 mm

Height H (imperial) 0.055 "

Height H (metric) 1.4 mm

Bundle Diameter min (imperial) 0.06 "

Bundle Diameter min (metric) 1.5 mm

Bundle Diameter max (imperial) 1.38 "

Bundle Diameter max (metric) 35.0 mm

Thickness T (imperial) 0.05 "

Thickness T (Metric) 1.2 mm

### Logistics and Packaging

Quantity per bag

Package Quantity 100

**Carton Quantity** 5000

**Weight (Metric)** 1.2 kg

## Material and Specifications

---

**Material** Polyamide 6.6 (PA66)

**Material Shortcut** PA66

**CSA Certified** No

**Flammability** UL94 V2

**Operating Temperature** -40 °F to +185 °F (-40 °C to +85 °C)

**ROHS Conformity** Yes

**Certification / Specification** UL

**UL Listed (US and Canada)** No

**UL Recognized (US and Canada)** Yes