

S2CM258HIRHSH1



Article Number: 151-29400

Two Way Saddle Mount, Max Bundle Diameter 3.5", Stud Diameter 0.25", PA66HIRHS, Gray, 500/pkg

 **RoHS**

Base Data

Local Order Number	S2CM258HIRHSH1
Type	S2CM25
Color	Gray (GY)
Features and Benefits	• Two way saddle separates bundles from wear and chafing. • Socket counterbore allows securing with a socket wrench from the top side for use with a weld stud or bolt. • Made from impact modified, heat stabilized, UV resistant material making it ideal for heavy duty applications.
Product Description	HellermannTyton's saddle mount can be installed between two bundles (such as wires, cables, hoses, tubing, conduit, etc...) to separate them and prevent chafing and wear. Fastened to a frame rail or mounting bracket, this "H" profile on the saddle mount provides a tight circumferential loop on large and small bundles.
Fixation Method (FF)	Screw Mounting and Rivet
Short Description	Two Way Saddle Mount, Max Bundle Diameter 3.5", Stud Diameter 0.25", PA66HIRHS, Gray, 500/pkg

Product Dimensions

Length L (imperial)	1.8 "
Length L (metric)	45.0 mm
Width W (imperial)	1.2 "
Width W (metric)	30.0 mm
Cable Tie Width Max (imperial)	0.5 "
Cable Tie Width max. (metric)	12.5 mm
Height H (imperial)	0.9 "
Height H (metric)	23.0 mm
Height H2 (imperial)	0.6 "
Height H2 (metric)	15.0 mm
Bundle Diameter max (imperial)	3.5 "
Bundle Diameter max (metric)	89.0 mm
Mounting Hole Diameter D (imperial)	0.24 "
Mounting Hole Diameter D (metric)	6.0 mm
Stud Size (Imperial)	0.25 "
Stud Size (Metric)	6.35 mm

Logistics and Packaging

Quantity per	bag
Package Quantity	500
Carton Quantity	500

Material and Specifications

Material	Polyamide 6.6 high impact modified, heat stabilized, UV resistant (PA66HIRHS)
Material Shortcut	PA66HIRHS
Flammability	UL94 HB
Operating Temperature	-40 °F to +230 °F (-40 °C to +110 °C)
ROHS Conformity	Yes