


S3STM500HIRHSC2



Article Number: 151-29500

Fir Tree Saddle Mount, Hole Diameter 0.5", Panel Thickness 0.08" - 0.52", PA66HIRHS, Black, 100/pkg

 RoHS

Base Data

Local Order Number	S3STM500HIRHSC2
Type	S3STM50
Color	Black (BK)
Features and Benefits	<ul style="list-style-type: none">• Heavy duty fir tree mount provides low insertion force and high extraction force.• Impact modified, heat stabilized, UV material make it ideal for heavy duty solutions
Product Description	The saddle mounts act as a standoff, elevating bundles above bolt protrusions commonly found in frame rails and panels. A tension tab on the mount allows cable ties to be pre-assembled in a ready position prior to bundles being brought to the mount. The mount can secure up to four separate bundles, providing parallel spacing between the frame rail and adjacent bundles. For use with HellermannTyton T50 - T255 ties.
Fixation Method (FF)	with Fir Tree (Mounts)
Short Description	Fir Tree Saddle Mount, Hole Diameter 0.5", Panel Thickness 0.08" - 0.52", PA66HIRHS, Black, 100/pkg

Product Dimensions

Length L (imperial)	2.0 "	
Length L (metric)	50.0 mm	
Bundle Diameter 2nd Loop max (imperial)	5.0 "	Width W (imperial)0.9 "
Width W (metric)	22.0 mm	
Height H (imperial)	1.4 "	
Height H (metric)	35.0 mm	
Height H2 (imperial)	2.2 "	
Height H2 (metric)	55.0 mm	
Bundle Diameter min (imperial)	5.0 "	
Bundle Diameter min (metric)	127.0 mm	
Bundle Diameter max (imperial)	5.0 "	
Bundle Diameter max (metric)	127.0 mm	
Panel Thickness max. (imperial)	0.5 "	
Panel Thickness max. (metric)	13.0 mm	
Panel Thickness min. (imperial)	0.07 "	
Panel Thickness min. (metric)	1.9 mm	
Mounting Hole Diameter D (imperial)	0.5 "	
Mounting Hole Diameter D (metric)	12.7 mm	
Bundle Diameter 1st Loop max (imperial)	5.0 "	Bundle Diameter 1st Loop max (metric)127.0 mm
Bundle Diameter 2nd Loop max	127.0 mm	

Logistics and Packaging

Quantity per	bag
Package Quantity	100
Carton Quantity	100

Material and Specifications

Material	Polyamide 6.6 high impact modified, heat stabilized, UV resistant (PA66HIRHS)
Material Shortcut	PA66HIRHS
Flammability	UL94 HB
Minimum Extraction Force (Imperial)	200.0 lbs
Minimum Extraction Force (Metric)	890 N
Operating Temperature	-40 °F to +230 °F (-40 °C to +110 °C)
ROHS Conformity	Yes