

## SNP2GHS0C2



**Article Number:** 192-10020

**Snapper Hose Clamps, .365"/.408" Min/Max Diameter, PA66GF13%, Black, 100/pkg**



### Base Data

**Local Order Number** SNP2GHS0C2

**Type** SNP2

**Color** Black (BK)

**Features and Benefits**

- Designed for quick, ratcheted installation and can be released and reused.
- Heat stabilized material is suitable for high temperature applications.

**Product Description** HellermannTyton snapper hose clamps are designed to provide a quick, ratcheted closure reducing installation time. The design also allows the clamp to be easily removed and re-applied when necessary. Snappers are made of high performing materials providing stability in a variety of diverse environments. Available in 32 standard sizes.

**Fixation Method (FF)** Plug-in mounting

**Variant** Closed

**Short Description** Snapper Hose Clamps, .365"/.408" Min/Max Diameter, PA66GF13%, Black, 100/pkg

### Product Dimensions

**Width W min (imperial)** 0.481 "

**Width W min (metric)** 12.22 mm

**Width W Max (imperial)** 0.688 "

**Width W max (metric)** 17.48 mm

**Width W2 (imperial)** 0.231 "

**Width W2 (metric)** 5.87 mm

**Bundle Diameter min (imperial)** 0.37 "

**Bundle Diameter min (metric)** 9.3 mm

**Bundle Diameter max (imperial)** 0.4 "

**Bundle Diameter max (metric)** 10.5 mm

**Diameter min. (imperial)** 0.365 "

**Diameter min. (metric)** 9.27 mm

**Diameter max. (imperial)** 0.408 "

**Diameter max. (metric)** 10.36 mm

**Nominal Diameter (imperial)** 0.39 "

**Nominal Diameter (metric)** 10 mm

**Wall Thickness WT (imperial)** 0.068 "

**Wall Thickness WT (metric)** 1.7 mm

### Logistics and Packaging

**Quantity per** bag

**Package Quantity** 100

**Carton Quantity** 100 Pieces

**Weight (Metric)** 0.14 kg

## Material and Specifications

---

**Material** Polyamide 6.6 glass filled impact modified heat stabilized (PA66GF13%)

**Material Shortcut** PA66GF13

**Flammability** UL94 HB

**Operating Temperature** -40 °F to +221 °F (-40 °C to +105 °C)

**ROHS Conformity** Yes