

## SNP3610K2



**Article Number:** 190-00157

**Snapper Hose Clamps, 1.459"/1.689" Min/Max Diameter, POM, White, 50/pkg**



### Base Data

**Local Order Number** SNP3610K2

**Type** SNP36

**Color** White (WH)

**Features and Benefits**

- Designed for quick, ratcheted installation and can be released and reused.
- Polyacetal material resists chemicals, corrosion and UV rays making it suitable for extreme environments.

**Product Description** HellermannTyton snapper hose clamps are designed to provide a quick, ratcheted closure reducing installation time. The design also allows the clamp to be easily removed and re-applied when necessary. Snappers are made of high performing materials providing stability in a variety of diverse environments. Available in 32 standard sizes.

**Fixation Method (FF)** Plug-in mounting

**Variant** Closed

**Short Description** Snapper Hose Clamps, 1.459"/1.689" Min/Max Diameter, POM, White, 50/pkg

### Product Dimensions

**Width W min (imperial)** 1.246 "

**Width W min (metric)** 31.65 mm

**Width W Max (imperial)** 2.047 "

**Width W max (metric)** 51.99 mm

**Width W2 (imperial)** 0.289 "

**Width W2 (metric)** 7.34 mm

**Bundle Diameter min (imperial)** 1.5 "

**Bundle Diameter min (metric)** 38.0 mm

**Bundle Diameter max (imperial)** 1.7 "

**Bundle Diameter max (metric)** 43.5 mm

**Diameter min. (imperial)** 1.459 "

**Diameter min. (metric)** 37.06 mm

**Diameter max. (imperial)** 1.689 "

**Diameter max. (metric)** 42.9 mm

**Wall Thickness WT (imperial)** 0.067 "

**Wall Thickness WT (metric)** 1.7 mm

### Logistics and Packaging

**Quantity per** bag

**Package Quantity** 50

**Carton Quantity** 1000

## Material and Specifications

---

|                              |                                      |
|------------------------------|--------------------------------------|
| <b>Material</b>              | Polyacetal (POM)                     |
| <b>Material Shortcut</b>     | POM                                  |
| <b>Flammability</b>          | UL94 HB                              |
| <b>Operating Temperature</b> | -40 °F to +185 °F (-40 °C to +85 °C) |
| <b>ROHS Conformity</b>       | Yes                                  |