

## SNP50GHS0C2



**Article Number:** 192-10500

**Snapper Hose Clamps, 2.055"/2.307" Min/Max Diameter, PA66GF13%, Black, 100/pkg**



### Base Data

<b>Local Order Number</b>	SNP50GHS0C2
<b>Type</b>	SNP50
<b>Color</b>	Black (BK)
<b>Features and Benefits</b>	<ul style="list-style-type: none"> <li>• Designed for quick, ratcheted installation and can be released and reused.</li> <li>• Heat stabilized material is suitable for high temperature applications.</li> </ul>
<b>Product Description</b>	HellermannTyton snapper hose clamps are designed to provide a quick, ratcheted closure reducing installation time. The design also allows the clamp to be easily removed and re-applied when necessary. Snappers are made of high performing materials providing stability in a variety of diverse environments. Available in 32 standard sizes.
<b>Fixation Method (FF)</b>	Plug-in mounting
<b>Variant</b>	Closed
<b>Short Description</b>	Snapper Hose Clamps, 2.055"/2.307" Min/Max Diameter, PA66GF13%, Black, 100/pkg

### Product Dimensions

<b>Width W min (imperial)</b>	1.437 "
<b>Width W min (metric)</b>	36.5 mm
<b>Width W Max (imperial)</b>	2.378 "
<b>Width W max (metric)</b>	60.4 mm
<b>Width W2 (imperial)</b>	0.295 "
<b>Width W2 (metric)</b>	7.49 mm
<b>Bundle Diameter min (imperial)</b>	2.05 "
<b>Bundle Diameter min (metric)</b>	52.2 mm
<b>Bundle Diameter max (imperial)</b>	2.3 "
<b>Bundle Diameter max (metric)</b>	58.6 mm
<b>Diameter min. (imperial)</b>	2.055 "
<b>Diameter min. (metric)</b>	52.2 mm
<b>Diameter max. (imperial)</b>	2.307 "
<b>Diameter max. (metric)</b>	58.6 mm
<b>Wall Thickness WT (imperial)</b>	0.068 "
<b>Wall Thickness WT (metric)</b>	1.7 mm

### Logistics and Packaging

<b>Quantity per</b>	bag
<b>Package Quantity</b>	100
<b>Carton Quantity</b>	600
<b>Weight (Metric)</b>	0.52 kg

## Material and Specifications

---

<b>Material</b>	Polyamide 6.6 glass filled impact modified heat stabilized (PA66GF13%)
<b>Material Shortcut</b>	PA66GF13
<b>Flammability</b>	UL94 HB
<b>Operating Temperature</b>	-40 °F to +221 °F (-40 °C to +105 °C)
<b>ROHS Conformity</b>	Yes