

## SNP6GHS0C2



Article Number: 192-10060

Snapper Hose Clamps, .458"/.518" Min/Max Diameter, PA66GF13%, Black, 100/pkg



### Base Data

Local Order Number SNP6GHS0C2

Type SNP6

Color Black (BK)

**Features and Benefits**

- Designed for quick, ratcheted installation and can be released and reused.
- Heat stabilized material is suitable for high temperature applications.

**Product Description** HellermannTyton snapper hose clamps are designed to provide a quick, ratcheted closure reducing installation time. The design also allows the clamp to be easily removed and re-applied when necessary. Snappers are made of high performing materials providing stability in a variety of diverse environments. Available in 32 standard sizes.

Fixation Method (FF) Plug-in mounting

Variant Closed

Short Description Snapper Hose Clamps, .458"/.518" Min/Max Diameter, PA66GF13%, Black, 100/pkg

### Product Dimensions

Width W min (imperial) 0.579 "

Width W min (metric) 14.71 mm

Width W Max (imperial) 0.848 "

Width W max (metric) 21.54 mm

Width W2 (imperial) 0.233 "

Width W2 (metric) 5.92 mm

Bundle Diameter min (imperial) 0.437 "

Bundle Diameter min (metric) 11.7 mm

Bundle Diameter max (imperial) 0.52 "

Bundle Diameter max (metric) 13.3 mm

Diameter min. (imperial) 0.458 "

Diameter min. (metric) 11.63 mm

Diameter max. (imperial) 0.518 "

Diameter max. (metric) 13.16 mm

Nominal Diameter (imperial) 0.512 "

Nominal Diameter (metric) 13 mm

Wall Thickness WT (imperial) 0.07 "

Wall Thickness WT (metric) 1.7 mm

### Logistics and Packaging

Quantity per bag

Package Quantity 100

**Carton Quantity** 100 Pieces

**Weight (Metric)** 0.2 kg

---

## Material and Specifications

---

**Material** Polyamide 6.6 glass filled impact modified heat stabilized (PA66GF13%)

**Material Shortcut** PA66GF13

**Flammability** UL94 HB

**Operating Temperature** -40 °F to +221 °F (-40 °C to +105 °C)

**ROHS Conformity** Yes