

## SR255X0HIHSUVH1

Article Number: 115-42100

Releasable Cable Tie, 14.6" Long, 250 lb Tensile Strength, PA66HIRHSUV, Black, 500/plain pkg



### Base Data

Local Order Number SR255X0HIHSUVH1

Type SR255X

Color Black (BK)

**Features and Benefits**

- High impact, heat and UV stabilized releasable cable ties contain an impact modifier allowing greater flexibility and greater resistance to vibration.
- Special design offers a release feature for quick and easy access to wire bundles.
- Head design provides high tensile strength with very low insertion force even after repeated use.

**Product Description** HellermannTyton releasable cable ties offer a release feature in the head allowing for easy access to wire bundles when changes are necessary. The head design guarantees high tensile strength even after repeated use, as well as a low insertion force. For high volume applications, tensioning tools are available to ensure consistent and safe installation.

Fixation Method (FF) None

Identification Plate Position none

Releasable Closure (Yes/No) Yes

Short Description Releasable Cable Tie, 14.6" Long, 250 lb Tensile Strength, PA66HIRHSUV, Black, 500/plain pkg

### Product Dimensions

Minimum Tensile Strength (imperial) 250.0 lbs

Minimum Tensile Strength (N) 1115.0 N

Length L (imperial) 14.6 "

Length L (metric) 370.0 mm

Width W (imperial) 0.5 "

Width W (metric) 12.6 mm

Bundle Diameter min (imperial) 0.51 "

Bundle Diameter min (metric) 13.0 mm

Bundle Diameter max (imperial) 3.9 "

Bundle Diameter max (metric) 100.0 mm

### Logistics and Packaging

Quantity per bag

Package Quantity 500

Carton Quantity 500

### Material and Specifications

Material Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)

Material Shortcut PA66HIRHSUV

**Flammability** UL94 HB

**Operating Temperature** -40 °F to +230 °F (-40 °C to +110 °C)

**ROHS Conformity** Yes