

## SR255X0HIHSUVX2

**Article Number:** 115-42101

**Releasable Cable Tie, 14.6" Long, 250 lb Tensile Strength, PA66HIRHSUV, Black, 25/pkg**



### Base Data

**Local Order Number** SR255X0HIHSUVX2

**Type** SR255X

**Color** Black (BK)

**Features and Benefits**

- High impact, heat and UV stabilized releasable cable ties contain an impact modifier allowing greater flexibility and greater resistance to vibration.
- Special design offers a release feature for quick and easy access to wire bundles.
- Head design provides high tensile strength with very low insertion force even after repeated use.

**Product Description** HellermannTyton releasable cable ties offer a release feature in the head allowing for easy access to wire bundles when changes are necessary. The head design guarantees high tensile strength even after repeated use, as well as a low insertion force. For high volume applications, tensioning tools are available to ensure consistent and safe installation.

**Fixation Method (FF)** None

**Identification Plate Position** none

**Releasable Closure (Yes/No)** Yes

**Short Description** Releasable Cable Tie, 14.6" Long, 250 lb Tensile Strength, PA66HIRHSUV, Black, 25/pkg

### Product Dimensions

**Minimum Tensile Strength (imperial)** 250.0 lbs

**Minimum Tensile Strength (N)** 1115.0 N

**Length L (imperial)** 14.6 "

**Length L (metric)** 370.0 mm

**Width W (imperial)** 0.5 "

**Width W (metric)** 12.6 mm

**Cable Tie Width Max (imperial)** 0.49 "

**Cable Tie Width max. (metric)** 12.5 mm

**Bundle Diameter min (imperial)** 0.51 "

**Bundle Diameter min (metric)** 13.0 mm

**Bundle Diameter max (imperial)** 3.9 "

**Bundle Diameter max (metric)** 100.0 mm

### Logistics and Packaging

**Quantity per** bag

**Package Quantity** 25

**Carton Quantity** 500

**Weight (Metric)** 6.25 kg

## Material and Specifications

---

<b>Material</b>	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
<b>Material Shortcut</b>	PA66HIRHSUV
<b>Flammability</b>	UL94 HB
<b>Operating Temperature</b>	-40 °F to +230 °F (-40 °C to +110 °C)
<b>ROHS Conformity</b>	Yes