

## T120LOHSK2



**Article Number:** 111-12450

**Heavy Duty Cable Tie, 30" Long, 120lb Tensile Strength, PA66HS, Black, 50/pkg**



### Base Data

**Local Order Number** T120LOHSK2

**Type** T120L

**Color** Black (BK)

- Features and Benefits**
- Heat stabilized heavy duty cable ties provide excellent resistance to high heat exposures.
  - Head design provides high tensile strength with very low insertion force.
  - Bent tail ensures a quick and simple installation.

**Product Description** HellermannTyton heavy duty cable ties offer a higher tensile strength for heavy load applications. The head design guarantees high tensile strength, as well as a low insertion force. The bent tail design allows quick and simple installations by hand. For high volume applications, tensioning tools are available to ensure consistent and safe installation.

**Fixation Method (FF)** None

**Identification Plate Position** none

**Releasable Closure (Yes/No)** No

**Tie Closure** plastic pawl

**Variant** Inside Serrated

**Short Description** Heavy Duty Cable Tie, 30" Long, 120lb Tensile Strength, PA66HS, Black, 50/pkg

### Product Dimensions

**Minimum Tensile Strength (imperial)** 120.0 lbs

**Minimum Tensile Strength (N)** 535.0 N

**Length L (imperial)** 30.0 "

**Length L (metric)** 760.0 mm

**Width W (imperial)** 0.3 "

**Width W (metric)** 7.6 mm

**Bundle Diameter min (imperial)** 0.23 "

**Bundle Diameter min (metric)** 5.76 mm

**Bundle Diameter max (imperial)** 8.85 "

**Bundle Diameter max (metric)** 225.0 mm

### Logistics and Packaging

**Quantity per** bag

**Package Quantity** 50

**Carton Quantity** 1000

**Weight (Metric)** 2.48 kg

### Material and Specifications

<b>Material</b>	Polyamide 6.6 heat stabilized (PA66HS)
<b>Material Shortcut</b>	PA66HS
<b>CSA Certified</b>	No
<b>Flammability</b>	UL94 V2
<b>Halogenfree</b>	Yes
<b>Operating Temperature</b>	-40 °F to +257 °F (-40 °C to +125 °C)
<b>ROHS Conformity</b>	Yes
<b>Certification / Specification</b>	UL ZODZ2.E64139 MIL 53421 VG U48/04103
<b>UL Listed (US and Canada)</b>	Yes
<b>UL Recognized (US and Canada)</b>	Yes