

## T120MR0H4

Article Number: 113-00011

Screw Mount Tie, 120lb, 4.3" Long, Max Bun Diameter 4.02", #1/4 Screw, PA66, Black, 500/pkg



### Base Data

Local Order Number T120MR0H4

Type T120MR

Color Black (BK)

**Features and Benefits**

- Part design applies easily to any #1/4" Screw
- Stud style provides low insertion and high extraction force.

**Product Description** Screw Mount Cable Ties are made of all plastic and provide a quick and simple method of mounting.

**Fixation Method (FF)** fixing hole

**Identification Plate Position** none

**Releasable Closure (Yes/No)** No

**Tie Closure** plastic pawl

**Variant** Inside Serrated

**Short Description** Screw Mount Tie, 120lb, 4.3" Long, Max Bun Diameter 4.02", #1/4 Screw, PA66, Black, 500/pkg

### Product Dimensions

**Minimum Tensile Strength (imperial)** 120.0 lbs

**Minimum Tensile Strength (N)** 535 N

**Length L (imperial)** 15.6 "

**Length L (metric)** 395.0 mm

**Width W (imperial)** 0.3 "

**Width W (metric)** 7.6 mm

**Height H (imperial)** 0.31 "

**Height H (metric)** 7.9 mm

**Bundle Diameter min (imperial)** 0.2 "

**Bundle Diameter min (metric)** 5.0 mm

**Bundle Diameter max (imperial)** 4.0 "

**Bundle Diameter max (metric)** 102.0 mm

**Mounting Hole Diameter D (imperial)** 0.26 "

**Mounting Hole Diameter D (metric)** 6.5 mm

**Thickness T (imperial)** 0.07 "

**Thickness T (Metric)** 1.8 mm

### Logistics and Packaging

**Quantity per** bag

**Package Quantity** 500

Carton Quantity 1000

## Material and Specifications

---

**Material** Polyamide 6.6 (PA66)

**Material Shortcut** PA66

**CSA Certified** No

**Flammability** UL94 V2

**Operating Temperature** -40 °F to +221 °F (-40 °C to +105 °C)

**ROHS Conformity** Yes

**UL Listed (US and Canada)** No

**UL Recognized (US and Canada)** Yes