

## T120MR0UVK2

Article Number: 113-12060

Screw Mount Tie, 18lb, 4.3" Long, Max Bun Diameter 4.02", #1/4 Screw, PA66HIRSUV, Black, 50/pkg



### Base Data

Local Order Number	T120MR0UVK2
Type	T120MR
Color	Black (BK)
Features and Benefits	<ul style="list-style-type: none"> <li>• Part design applies easily to any #1/4" Screw</li> <li>• Stud style provides low insertion and high extraction force.</li> </ul>
Product Description	Screw Mount Cable Ties are made of all plastic and provide a quick and simple method of mounting.
Fixation Method (FF)	fixing hole
Identification Plate Position	none
Mounting Screw Type	M6
Releasable Closure (Yes/No)	No
Tie Closure	plastic pawl
Variant	Inside Serrated
Short Description	Screw Mount Tie, 18lb, 4.3" Long, Max Bun Diameter 4.02", #1/4 Screw, PA66HIRSUV, Black, 50/pkg

### Product Dimensions

Minimum Tensile Strength (imperial)	120.0 lbs
Minimum Tensile Strength (N)	535 N
Length L (imperial)	15.6 "
Length L (metric)	395.0 mm
Width W (imperial)	0.3 "
Width W (metric)	7.6 mm
Height H (imperial)	0.31 "
Height H (metric)	7.9 mm
Bundle Diameter min (imperial)	0.2 "
Bundle Diameter min (metric)	5.0 mm
Bundle Diameter max (imperial)	4.0 "
Bundle Diameter max (metric)	102.0 mm
Mounting Hole Diameter D (imperial)	0.26 "
Mounting Hole Diameter D (metric)	6.5 mm
Thickness T (imperial)	0.07 "
Cable Tie Head Height (Metric)	7.9 mm
Cable Tie Head Length (metric)	28.4 mm
Cable Tie Head Width (metric)	13.4 mm
Cable Tie Head Length (imperial)	1.12 "

**Cable Tie Head Width (imperial)** 0.51 "  
**Thickness T (Metric)** 1.8 mm

---

## Logistics and Packaging

---

**Quantity per** pc  
**Package Quantity** 50  
**Carton Quantity** 1000  
**Weight (Metric)** 5.8 kg

---

## Material and Specifications

---

**Material** Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)  
**Material Shortcut** PA66HIRHSUV  
**Flammability** UL94 HB  
**Operating Temperature** -40 °F to +230 °F (-40 °C to +110 °C)  
**ROHS Conformity** Yes