

## T120MR9K2



**Article Number:** 113-12029

**Screw Mount Tie, 18lb, 4.3" Long, Max Bun Diameter 4.02", #1/4 Screw, PA66, Natural, 50/pkg**



### Base Data

**Local Order Number** T120MR9K2

**Type** T120MR

**Color** Natural (NA)

**Features and Benefits**

- Part design applies easily to any #1/4" Screw
- Stud style provides low insertion and high extraction force.

**Product Description** Screw Mount Cable Ties are made of all plastic and provide a quick and simple method of mounting.

**Fixation Method (FF)** fixing hole

**Identification Plate Position** none

**Mounting Screw Type** M6

**Releasable Closure (Yes/No)** No

**Tie Closure** plastic pawl

**Variant** Inside Serrated

**Short Description** Screw Mount Tie, 18lb, 4.3" Long, Max Bun Diameter 4.02", #1/4 Screw, PA66, Natural, 50/pkg

### Product Dimensions

**Minimum Tensile Strength (imperial)** 120.0 lbs

**Minimum Tensile Strength (N)** 535 N

**Length L (imperial)** 15.6 "

**Length L (metric)** 395.0 mm

**Width W (imperial)** 0.3 "

**Width W (metric)** 7.6 mm

**Height H (imperial)** 0.31 "

**Height H (metric)** 7.9 mm

**Bundle Diameter min (imperial)** 0.2 "

**Bundle Diameter min (metric)** 5.0 mm

**Bundle Diameter max (imperial)** 4.0 "

**Bundle Diameter max (metric)** 102.0 mm

**Mounting Hole Diameter D (imperial)** 0.26 "

**Mounting Hole Diameter D (metric)** 6.5 mm

**Thickness T (imperial)** 0.07 "

**Cable Tie Head Height (Metric)** 7.9 mm

**Cable Tie Head Length (metric)** 28.4 mm

**Cable Tie Head Width (metric)** 13.4 mm

**Cable Tie Head Length (imperial)** 1.12 "

**Cable Tie Head Width (imperial)** 0.51 "  
**Thickness T (Metric)** 1.8 mm

---

## Logistics and Packaging

---

**Quantity per** bag  
**Package Quantity** 50  
**Carton Quantity** 50 Pieces  
**Weight (Metric)** 5.8 kg

---

## Material and Specifications

---

**Material** Polyamide 6.6 (PA66)  
**Material Shortcut** PA66  
**CSA Certified** No  
**Flammability** UL94 V2  
**Operating Temperature** -40 °F to +185 °F (-40 °C to +85 °C)  
**ROHS Conformity** Yes  
**UL Listed (US and Canada)** Yes  
**UL Recognized (US and Canada)** Yes