

T120R0HSK2



Article Number: 111-12061

Heavy Duty Cable Tie, 15.2" Long, 120lb Tensile Strength, PA66HS, Black, 50/pkg

 RoHS

Base Data

Local Order Number	T120R0HSK2
Type	T120R
Color	Black (BK)
Features and Benefits	- Heat stabilized heavy duty cable ties provide excellent resistance to high heat exposures. - Head design provides high tensile strength with very low insertion force. - Bent tail ensures a quick and simple installation.
Product Description	HellermannTyton heavy duty cable ties offer a higher tensile strength for heavy load applications. The head design guarantees high tensile strength, as well as a low insertion force. The bent tail design allows quick and simple installations by hand. For high volume applications, tensioning tools are available to ensure consistent and safe installation.
Fixation Method (FF)	None
Identification Plate Position	none
Releasable Closure (Yes/No)	No
Tie Closure	plastic pawl
Variant	Inside Serrated
Short Description	Heavy Duty Cable Tie, 15.2" Long, 120lb Tensile Strength, PA66HS, Black, 50/pkg

Product Dimensions

Minimum Tensile Strength (imperial)	120.0 lbs
Minimum Tensile Strength (N)	535.0 N
Length L (imperial)	15.2 "
Length L (metric)	387.0 mm
Width W (imperial)	0.3 "
Width W (metric)	7.6 mm
Bundle Diameter min (imperial)	0.2 "
Bundle Diameter min (metric)	5.0 mm
Bundle Diameter max (imperial)	4.1 "
Bundle Diameter max (metric)	105.0 mm

Logistics and Packaging

Quantity per	bag
Package Quantity	50
Carton Quantity	1000

Material and Specifications

Material	Polyamide 6.6 heat stabilized (PA66HS)
----------	--

Material Shortcut PA66HS

CSA Certified No

Flammability UL94 V2

Halogenfree Yes

Operating Temperature -40 °F to +257 °F (-40 °C to +125 °C)

ROHS Conformity Yes

Certification / Specification MIL 53421
VG U48/04103
UL ZODZ2.E64139

UL Listed (US and Canada) Yes

UL Recognized (US and Canada) Yes