

T120RDH0K2

Article Number: 117-05501

Double Head Tie, 15.7" Long, 50lb Tensile Strength, PA66, Black, 50/pkg



Base Data

Local Order Number T120RDH0K2

Type T120RDH

Color Black (BK)

- Features and Benefits**
- The tie contains a dual locking design to secure two bundles at once.
 - Head design can also provide spacing between parallel bundles.
 - Bent tail allows for quick insertion into head.

Product Description The double head cable tie was designed with a dual locking head to secure two bundles simultaneously. The head also provides separation between bundles or bundles running parallel to each other. The bent tail design allows quick and simple installations by hand. For high volume applications, tensioning tools are available to ensure consistent and safe installation.

Fixation Method (FF) None

Identification Plate Position none

Releasable Closure (Yes/No) No

Variant Inside Serrated

Short Description Double Head Tie, 15.7" Long, 50lb Tensile Strength, PA66, Black, 50/pkg

Product Dimensions

Minimum Tensile Strength (imperial) 120.0 lbs

Minimum Tensile Strength (N) 535.0 N

Length L (imperial) 15.7 "

Length L (metric) 398.0 mm

Bundle Diameter 2nd Loop max (imperial) 2.0 "

Width W (imperial) 0.3 "

Width W (metric) 7.6 mm

Bundle Diameter min (imperial) 0.19 "

Bundle Diameter min (metric) 4.6 mm

Bundle Diameter max (imperial) 2.0 "

Bundle Diameter max (metric) 50.8 mm

Bundle Diameter 1st Loop max (imperial) 4.0 "

Bundle Diameter 1st Loop max (metric) 101.6 mm

Bundle Diameter 2nd Loop max (metric) 50.8 mm

Logistics and Packaging

Quantity per bag

Package Quantity 50

Carton Quantity 1000

Material and Specifications

Material	Polyamide 6.6 (PA66)
Material Shortcut	PA66
CSA Certified	No
Flammability	UL94 V2
Operating Temperature	-40 °F to +185 °F (-40 °C to +85 °C)
ROHS Conformity	Yes
UL Listed (US and Canada)	No
UL Recognized (US and Canada)	Yes