

## T120RSM0HIRK2



**Article Number:** 157-01300

**Stud Mount Tie for 1/4", 120lb Tensile, 16.0" Long, PA66HIRHSUV, Black, 50/pkg**



### Base Data

<b>Local Order Number</b>	T120RSM0HIRK2
<b>Type</b>	T120RSM
<b>Color</b>	Black (BK)
<b>Features and Benefits</b>	<ul style="list-style-type: none"> <li>• Mounts and secures bundles all in one component; providing quick installation time.</li> <li>• Mounts quickly and securely for easy installation.</li> </ul>
<b>Product Description</b>	HellermannTyton stud mount tie designed for use on a 1/4" threaded stud or exposed threads of a machine screw.
<b>Fixation Method (FF)</b>	Weld Stud Fixing
<b>Identification Plate Position</b>	none
<b>Releasable Closure (Yes/No)</b>	No
<b>Tie Closure</b>	plastic pawl
<b>Variant</b>	Inside Serrated
<b>Short Description</b>	Stud Mount Tie for 1/4", 120lb Tensile, 16.0" Long, PA66HIRHSUV, Black, 50/pkg

### Product Dimensions

<b>Minimum Tensile Strength (imperial)</b>	120.0 lbs
<b>Minimum Tensile Strength (N)</b>	535 N
<b>Length L (imperial)</b>	16.0 "
<b>Length L (metric)</b>	405.0 mm
<b>Width W (imperial)</b>	0.3 "
<b>Width W (metric)</b>	7.6 mm
<b>Height H (imperial)</b>	0.77 "
<b>Height H (metric)</b>	19.5 mm
<b>Bundle Diameter min (imperial)</b>	0.2 "
<b>Bundle Diameter min (metric)</b>	5.0 mm
<b>Bundle Diameter max (imperial)</b>	4.0 "
<b>Bundle Diameter max (metric)</b>	101.0 mm
<b>Stud Size (Imperial)</b>	0.25 "
<b>Stud Size (Metric)</b>	6.3 mm

### Logistics and Packaging

<b>Quantity per</b>	bag
<b>Package Quantity</b>	50
<b>Carton Quantity</b>	1000

## Material and Specifications

---

<b>Material</b>	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
<b>Material Shortcut</b>	PA66HIRHSUV
<b>Flammability</b>	UL94 HB
<b>Operating Temperature</b>	-40 °F to +230 °F (-40 °C to +110 °C)
<b>ROHS Conformity</b>	Yes