

T120S0UVK2



Article Number: 111-12860

Heavy Duty Cable Tie, 8.9" Long, 120lb Tensile Strength, PA66UV, Black, 50/pkg



Base Data

Local Order Number T120S0UVK2

Type T120S

Color Black (BK)

- Features and Benefits**
- UV stabilized heavy duty cable ties contain an inhibitor which prolongs the life of the tie in UV exposures .
 - Head design provides high tensile strength with very low insertion force.
 - Bent tail ensures a quick and simple installation.

Product Description HellermannTyton heavy duty cable ties offer a higher tensile strength for heavy load applications. The head design guarantees high tensile strength, as well as a low insertion force. The bent tail design allows quick and simple installations by hand. For high volume applications, tensioning tools are available to ensure consistent and safe installation.

Fixation Method (FF) None

Identification Plate Position none

Releasable Closure (Yes/No) No

Tie Closure plastic pawl

Variant Inside Serrated

Short Description Heavy Duty Cable Tie, 8.9" Long, 120lb Tensile Strength, PA66UV, Black, 50/pkg

Product Dimensions

Minimum Tensile Strength (imperial) 120.0 lbs

Minimum Tensile Strength (N) 535.0 N

Length L (imperial) 8.9 "

Length L (metric) 225.0 mm

Width W (imperial) 0.3 "

Width W (metric) 7.6 mm

Bundle Diameter min (imperial) 0.2 "

Bundle Diameter min (metric) 5.0 mm

Bundle Diameter max (imperial) 2.2 "

Bundle Diameter max (metric) 55.0 mm

Thickness T (imperial) 0.06 "

Cable Tie Head Height (Metric) 7.7 mm

Cable Tie Head Length (metric) 10 mm

Cable Tie Head Width (metric) 13.2 mm

Cable Tie Head Length (imperial) 0.393 "

Cable Tie Head Width (imperial) 0.502 "

Thickness T (Metric) 1.6 mm

Logistics and Packaging

| | |
|-------------------------|-------------|
| Quantity per | pc |
| Package Quantity | 50 |
| Carton Quantity | 1500 Pieces |
| Weight (Metric) | 4.7 kg |

Material and Specifications

| | |
|--------------------------------------|--------------------------------------|
| Material | Polyamide 6.6 UV-resistant (PA66UV) |
| Material Shortcut | PA66UV |
| Flammability | UL94 V2 |
| Halogenfree | Yes |
| Operating Temperature | -40 °F to +185 °F (-40 °C to +85 °C) |
| ROHS Conformity | Yes |
| Certification / Specification | UL ZODZ2.E64139 |
| UL Listed (US and Canada) | No |
| UL Recognized (US and Canada) | No |