

## T150L0X2



Article Number: 111-15405

Heavy Duty Cable Tie, 32.3" Long, 175 lb Tensile Strength, PA66, Black, 25/pkg



### Base Data

Local Order Number T150L0X2

Type T150L

Color Black (BK)

**Features and Benefits**

- Heavy duty design to offer higher tensile strength.
- Head design provides high tensile strength with very low insertion force.

**Product Description** HellermannTyton heavy duty cable ties offer a higher tensile strength for heavy load applications. The head design guarantees high tensile strength, as well as a low insertion force. For high volume applications, tensioning tools are available to ensure consistent and safe installation.

Fixation Method (FF) None

Identification Plate Position none

Releasable Closure (Yes/No) No

Tie Closure plastic pawl

Variant Inside Serrated

Short Description Heavy Duty Cable Tie, 32.3" Long, 175 lb Tensile Strength, PA66, Black, 25/pkg

### Product Dimensions

Minimum Tensile Strength (imperial) 175.0 lbs

Minimum Tensile Strength (N) 780.0 N

Length L (imperial) 32.3 "

Length L (metric) 820.0 mm

Width W (imperial) 0.35 "

Width W (metric) 8.8 mm

Bundle Diameter min (imperial) 0.32 "

Bundle Diameter min (metric) 8.0 mm

Bundle Diameter max (imperial) 9.6 "

Bundle Diameter max (metric) 245.0 mm

### Logistics and Packaging

Quantity per bag

Package Quantity 25

Carton Quantity 500

### Material and Specifications

Material Polyamide 6.6 (PA66)

Material Shortcut PA66

**CSA Certified** No  
**Flammability** UL94 V2  
**Halogenfree** Yes  
**Operating Temperature** -40 °F to +185 °F (-40 °C to +85 °C)  
**ROHS Conformity** Yes  
**Certification / Specification** MIL 53421  
UL ZODZ2.E64139  
**UL Listed (US and Canada)** No  
**UL Recognized (US and Canada)** Yes