

T150L2X2



Article Number: 111-15407

Heavy Duty Cable Tie, 32.3" Long, 175 lb Tensile Strength, PA66, Red, 25/pkg

 RoHS

Base Data

|                               |                                                                                                                                                                                                                                                                                                 |
|-------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Local Order Number            | T150L2X2                                                                                                                                                                                                                                                                                        |
| Type                          | T150L                                                                                                                                                                                                                                                                                           |
| Color                         | Red (RD)                                                                                                                                                                                                                                                                                        |
| Features and Benefits         | <ul style="list-style-type: none"><li>• Heavy duty design to offer higher tensile strength.</li><li>• Head design provides high tensile strength with very low insertion force.</li></ul>                                                                                                       |
| Product Description           | HellermannTyton heavy duty cable ties offer a higher tensile strength for heavy load applications. The head design guarantees high tensile strength, as well as a low insertion force. For high volume applications, tensioning tools are available to ensure consistent and safe installation. |
| Fixation Method (FF)          | None                                                                                                                                                                                                                                                                                            |
| Identification Plate Position | none                                                                                                                                                                                                                                                                                            |
| Releasable Closure (Yes/No)   | No                                                                                                                                                                                                                                                                                              |
| Tie Closure                   | plastic pawl                                                                                                                                                                                                                                                                                    |
| Variant                       | Inside Serrated                                                                                                                                                                                                                                                                                 |
| Short Description             | Heavy Duty Cable Tie, 32.3" Long, 175 lb Tensile Strength, PA66, Red, 25/pkg                                                                                                                                                                                                                    |

Product Dimensions

|                                     |           |
|-------------------------------------|-----------|
| Minimum Tensile Strength (imperial) | 175.0 lbs |
| Minimum Tensile Strength (N)        | 780.0 N   |
| Length L (imperial)                 | 32.3 "    |
| Length L (metric)                   | 820.0 mm  |
| Width W (imperial)                  | 0.35 "    |
| Width W (metric)                    | 8.8 mm    |
| Bundle Diameter min (imperial)      | 0.32 "    |
| Bundle Diameter min (metric)        | 8.0 mm    |
| Bundle Diameter max (imperial)      | 9.6 "     |
| Bundle Diameter max (metric)        | 245.0 mm  |

Logistics and Packaging

|                  |     |
|------------------|-----|
| Quantity per     | bag |
| Package Quantity | 25  |
| Carton Quantity  | 500 |

Material and Specifications

|                   |                      |
|-------------------|----------------------|
| Material          | Polyamide 6.6 (PA66) |
| Material Shortcut | PA66                 |

|                                      |                                      |
|--------------------------------------|--------------------------------------|
| <b>CSA Certified</b>                 | No                                   |
| <b>Flammability</b>                  | UL94 V2                              |
| <b>Halogenfree</b>                   | Yes                                  |
| <b>Operating Temperature</b>         | -40 °F to +185 °F (-40 °C to +85 °C) |
| <b>ROHS Conformity</b>               | Yes                                  |
| <b>Certification / Specification</b> | MIL 53421<br>UL ZODZ2.E64139         |
| <b>UL Listed (US and Canada)</b>     | No                                   |
| <b>UL Recognized (US and Canada)</b> | Yes                                  |