

T150M0HSX2



Article Number: 111-15609

Heavy Duty Cable Tie, 21" Long, 175 lb Tensile Strength, PA66HS, Black, 25/pkg



Base Data

Local Order Number T150M0HSX2

Type T150M

Color Black (BK)

Features and Benefits

- Heat stabilized heavy duty cable ties provide excellent resistance to high heat exposures.
- Head design provides high tensile strength with very low insertion force

Product Description HellermannTyton heavy duty cable ties offer a higher tensile strength for heavy load applications. The head design guarantees high tensile strength, as well as a low insertion force. For high volume applications, tensioning tools are available to ensure consistent and safe installation.

Fixation Method (FF) None

Identification Plate Position none

Releasable Closure (Yes/No) No

Tie Closure plastic pawl

Variant Inside Serrated

Short Description Heavy Duty Cable Tie, 21" Long, 175 lb Tensile Strength, PA66HS, Black, 25/pkg

Product Dimensions

Minimum Tensile Strength (imperial) 175.0 lbs

Minimum Tensile Strength (N) 780.0 N

Length L (imperial) 21.0 "

Length L (metric) 530.0 mm

Width W (imperial) 0.35 "

Width W (metric) 8.9 mm

Bundle Diameter min (imperial) 0.32 "

Bundle Diameter min (metric) 8.0 mm

Bundle Diameter max (imperial) 5.9 "

Bundle Diameter max (metric) 150.0 mm

Thickness T (imperial) 0.079 "

Thickness T (Metric) 2 mm

Logistics and Packaging

Quantity per bag

Package Quantity 25

Carton Quantity 1000

Material and Specifications

Material	Polyamide 6.6 heat stabilized (PA66HS)
Material Shortcut	PA66HS
CSA Certified	No
Flammability	UL94 V2
Halogenfree	Yes
Operating Temperature	-40 °F to +257 °F (-40 °C to +125 °C)
ROHS Conformity	Yes
Certification / Specification	UL ZODZ2.E64139
UL Listed (US and Canada)	No
UL Recognized (US and Canada)	Yes