

T150R0UVX2



Article Number: 111-15206

Heavy Duty Cable Tie, 15.4" Long, 175 lb Tensile Strength, PA66UV, Black, 25/pkg



Base Data

Local Order Number T150R0UVX2

Type T150R(U)

Color Black (BK)

Features and Benefits

- UV stabilized heavy duty cable ties contain an inhibitor which prolongs the life of the tie in UV exposures .
- Head design provides high tensile strength with very low insertion force.

Product Description HellermannTyton heavy duty cable ties offer a higher tensile strength for heavy load applications. The head design guarantees high tensile strength, as well as a low insertion force. For high volume applications, tensioning tools are available to ensure consistent and safe installation.

Fixation Method (FF) None

Identification Plate Position none

Releasable Closure (Yes/No) No

Variant Inside Serrated

Short Description Heavy Duty Cable Tie, 15.4" Long, 175 lb Tensile Strength, PA66UV, Black, 25/pkg

Product Dimensions

Minimum Tensile Strength (imperial) 175.0 lbs

Minimum Tensile Strength (N) 780.0 N

Length L (imperial) 15.4 "

Length L (metric) 390.0 mm

Width W (imperial) 0.35 "

Width W (metric) 8.8 mm

Bundle Diameter min (imperial) 0.32 "

Bundle Diameter min (metric) 8.0 mm

Bundle Diameter max (imperial) 4.1 "

Bundle Diameter max (metric) 105.0 mm

Thickness T (imperial) 0.075 "

Cable Tie Head Height (Metric) 9.5 mm

Cable Tie Head Length (metric) 14 mm

Cable Tie Head Width (metric) 14 mm

Cable Tie Head Length (imperial) 0.55 "

Cable Tie Head Width (imperial) 0.55 "

Thickness T (Metric) 1.9 mm

Logistics and Packaging

Quantity per bag

Package Quantity 25
Carton Quantity 1000

Material and Specifications

Material Polyamide 6.6 UV-resistant (PA66UV)
Material Shortcut PA66UV
CSA Certified No
Flammability UL94 V2
Halogenfree Yes
Operating Temperature -40 °F to +185 °F (-40 °C to +85 °C)
ROHS Conformity Yes
Certification / Specification UL ZODZ2.E64139
UL Listed (US and Canada) No
UL Recognized (US and Canada) Yes