

T150XL0UVX2



Article Number: 111-15502

Heavy Duty Cable Tie, 43.1" Long, 175 lb Tensile Strength, PA66UV, Black, 25/pkg



Base Data

Local Order Number T150XL0UVX2

Type T150XL

Color Black (BK)

Features and Benefits

- UV stabilized heavy duty cable ties contain an inhibitor which prolongs the life of the tie in UV exposures .
- Head design provides high tensile strength with very low insertion force.

Product Description HellermannTyton heavy duty cable ties offer a higher tensile strength for heavy load applications. The head design guarantees high tensile strength, as well as a low insertion force. For high volume applications, tensioning tools are available to ensure consistent and safe installation.

Fixation Method (FF) None

Identification Plate Position none

Releasable Closure (Yes/No) No

Tie Closure plastic pawl

Variant Inside Serrated

Short Description Heavy Duty Cable Tie, 43.1" Long, 175 lb Tensile Strength, PA66UV, Black, 25/pkg

Product Dimensions

Minimum Tensile Strength (imperial) 175.0 lbs

Minimum Tensile Strength (N) 780.0 N

Length L (imperial) 43.1 "

Length L (metric) 1095.0 mm

Width W (imperial) 0.35 "

Width W (metric) 8.9 mm

Bundle Diameter min (imperial) 6.0 "

Bundle Diameter min (metric) 152.0 mm

Bundle Diameter max (imperial) 13.0 "

Bundle Diameter max (metric) 330.0 mm

Logistics and Packaging

Quantity per bag

Package Quantity 25

Carton Quantity 500 Pieces

Weight (Metric) 19 kg

Material and Specifications

Material Polyamide 6.6 UV-resistant (PA66UV)

Material Shortcut PA66UV
Flammability UL94 V2
Halogenfree Yes
Operating Temperature -40 °F to +185 °F (-40 °C to +85 °C)
ROHS Conformity Yes
Certification / Specification UL ZODZ2.E64139
UL Listed (US and Canada) No
UL Recognized (US and Canada) No