

T150XL9X2



Article Number: 111-15519

Heavy Duty Cable Tie, 43.1" Long, 175 lb Tensile Strength, PA66, Natural, 25/pkg



Base Data

Local Order Number T150XL9X2

Type T150XL

Color Natural (NA)

- Features and Benefits**
- Heavy duty design to offer higher tensile strength.
 - Head design provides high tensile strength with very low insertion force.

Product Description HellermannTyton heavy duty cable ties offer a higher tensile strength for heavy load applications. The head design guarantees high tensile strength, as well as a low insertion force. For high volume applications, tensioning tools are available to ensure consistent and safe installation.

Fixation Method (FF) None

Identification Plate Position none

Releasable Closure (Yes/No) No

Tie Closure plastic pawl

Variant Inside Serrated

Short Description Heavy Duty Cable Tie, 43.1" Long, 175 lb Tensile Strength, PA66, Natural, 25/pkg

Product Dimensions

Minimum Tensile Strength (imperial) 175.0 lbs

Minimum Tensile Strength (N) 780.0 N

Length L (imperial) 43.1 "

Length L (metric) 1095.0 mm

Width W (imperial) 0.35 "

Width W (metric) 8.9 mm

Bundle Diameter min (imperial) 6.0 "

Bundle Diameter min (metric) 152.0 mm

Bundle Diameter max (imperial) 13.0 "

Bundle Diameter max (metric) 330.0 mm

Thickness T (imperial) 0.083 "

Thickness T (Metric) 2.1 mm

Logistics and Packaging

Quantity per bag

Package Quantity 25

Carton Quantity 500

Weight (Metric) 20.8 kg

Material and Specifications

Material	Polyamide 6.6 (PA66)
Material Shortcut	PA66
CSA Certified	No
Flammability	UL94 V2
Halogenfree	Yes
Operating Temperature	-40 °F to +185 °F (-40 °C to +85 °C)
ROHS Conformity	Yes
Certification / Specification	Det Norske Veritas UL ZODZ2.E64139
UL Listed (US and Canada)	No
UL Recognized (US and Canada)	Yes