

T150XLL0UVX2



Article Number: 111-15305

Heavy Duty Cable Tie, 52.2" Long, 175 lb Tensile Strength, PA66UV, Black, 25/pkg



Base Data

Local Order Number	T150XLL0UVX2
Type	T150XLL
Color	Black (BK)
Features and Benefits	• UV stabilized heavy duty cable ties contain an inhibitor which prolongs the life of the tie in UV exposures . • Head design provides high tensile strength with very low insertion force.
Product Description	HellermannTyton heavy duty cable ties offer a higher tensile strength for heavy load applications. The head design guarantees high tensile strength, as well as a low insertion force. For high volume applications, tensioning tools are availableto ensure consistent and safe installation.
Fixation Method (FF)	None
Identification Plate Position	none
Releasable Closure (Yes/No)	No
Tie Closure	plastic pawl
Variant	Inside Serrated
Short Description	Heavy Duty Cable Tie, 52.2" Long, 175 lb Tensile Strength, PA66UV, Black, 25/pkg

Product Dimensions

Minimum Tensile Strength (imperial)	175.0 lbs
Minimum Tensile Strength (N)	780.0 N
Length L (imperial)	52.2 "
Length L (metric)	1325.0 mm
Width W (imperial)	0.35 "
Width W (metric)	8.9 mm
Bundle Diameter min (imperial)	6.0 "
Bundle Diameter min (metric)	152.0 mm
Bundle Diameter max (imperial)	16.0 "
Bundle Diameter max (metric)	405.0 mm
Thickness T (imperial)	0.083 "
Cable Tie Head Height (Metric)	9.5 mm
Cable Tie Head Length (metric)	14 mm
Cable Tie Head Width (metric)	14 mm
Cable Tie Head Length (imperial)	0.55 "
Cable Tie Head Width (imperial)	0.55 "
Thickness T (Metric)	2.1 mm

Logistics and Packaging

Quantity per	bag
Package Quantity	25
Carton Quantity	500

Material and Specifications

Material	Polyamide 6.6 UV-resistant (PA66UV)
Material Shortcut	PA66UV
Flammability	UL94 V2
Halogenfree	Yes
Operating Temperature	-40 °F to +185 °F (-40 °C to +85 °C)
ROHS Conformity	Yes
Certification / Specification	UL ZODZ2.E64139
UL Listed (US and Canada)	No
UL Recognized (US and Canada)	No