

T150XLL4X2



Article Number: 111-15302

Heavy Duty Cable Tie, 52.2" Long, 175 lb Tensile Strength, PA66, Yellow, 25/pkg



Base Data

Local Order Number T150XLL4X2

Type T150XLL

Color Yellow (YE)

- Features and Benefits**
- Heavy duty design to offer higher tensile strength.
 - Head design provides high tensile strength with very low insertion force.

Product Description HellermannTyton heavy duty cable ties offer a higher tensile strength for heavy load applications. The head design guarantees high tensile strength, as well as a low insertion force. For high volume applications, tensioning tools are available to ensure consistent and safe installation.

Fixation Method (FF) None

Identification Plate Position none

Releasable Closure (Yes/No) No

Tie Closure plastic pawl

Variant Inside Serrated

Short Description Heavy Duty Cable Tie, 52.2" Long, 175 lb Tensile Strength, PA66, Yellow, 25/pkg

Product Dimensions

Minimum Tensile Strength (imperial) 175.0 lbs

Minimum Tensile Strength (N) 780.0 N

Length L (imperial) 52.2 "

Length L (metric) 1325.0 mm

Width W (imperial) 0.35 "

Width W (metric) 8.9 mm

Bundle Diameter min (imperial) 6.0 "

Bundle Diameter min (metric) 152.0 mm

Bundle Diameter max (imperial) 16.0 "

Bundle Diameter max (metric) 405.0 mm

Logistics and Packaging

Quantity per bag

Package Quantity 25

Carton Quantity 500

Material and Specifications

Material Polyamide 6.6 (PA66)

Material Shortcut PA66

CSA Certified No
Flammability UL94 V2
Halogenfree Yes
Operating Temperature -40 °F to +185 °F (-40 °C to +85 °C)
ROHS Conformity Yes
Certification / Specification UL ZODZ2.E64139
UL Listed (US and Canada) No
UL Recognized (US and Canada) Yes