

## T18MR0C2



**Article Number:** 113-00022

**Screw Mount Tie, 18lb 4.3" Long, Max Bun Diameter .79", #4 Screw PA66, Black, 100/pkg**



### Base Data

<b>Local Order Number</b>	T18MR0C2
<b>Type</b>	T18MR
<b>Color</b>	Black (BK)
<b>Features and Benefits</b>	<ul style="list-style-type: none"> <li>• Mount design secures firmly on any #4 Screw</li> <li>• Screw mount style creates low insertion and high extraction force.</li> </ul>
<b>Product Description</b>	Screw Mount Cable Ties are made of all plastic and provide a quick and simple method of mounting.
<b>Fixation Method (FF)</b>	fixing hole
<b>Identification Plate Position</b>	none
<b>Releasable Closure (Yes/No)</b>	No
<b>Tie Closure</b>	plastic pawl
<b>Variant</b>	Inside Serrated
<b>Short Description</b>	Screw Mount Tie, 18lb 4.3" Long, Max Bun Diameter .79", #4 Screw PA66, Black, 100/pkg

### Product Dimensions

<b>Minimum Tensile Strength (imperial)</b>	18.0 lbs
<b>Minimum Tensile Strength (N)</b>	80 N
<b>Length L (imperial)</b>	4.3 "
<b>Length L (metric)</b>	110.0 mm
<b>Width W (imperial)</b>	0.1 "
<b>Width W (metric)</b>	2.5 mm
<b>Height H (imperial)</b>	0.17 "
<b>Height H (metric)</b>	4.2 mm
<b>Bundle Diameter min (imperial)</b>	0.06 "
<b>Bundle Diameter min (metric)</b>	1.5 mm
<b>Bundle Diameter max (imperial)</b>	0.8 "
<b>Bundle Diameter max (metric)</b>	20.0 mm
<b>Mounting Hole Diameter D (imperial)</b>	0.12 "
<b>Mounting Hole Diameter D (metric)</b>	3.1 mm
<b>Thickness T (imperial)</b>	0.039 "
<b>Thickness T (Metric)</b>	1.0 mm

### Logistics and Packaging

<b>Quantity per</b>	bag
<b>Package Quantity</b>	100

Carton Quantity 10000

## Material and Specifications

---

<b>Material</b>	Polyamide 6.6 heat stabilized (PA66HS)
<b>Material Shortcut</b>	PA66HS
<b>CSA Certified</b>	No
<b>Flammability</b>	UL94 V2
<b>Operating Temperature</b>	-40 °F to +221 °F (-40 °C to +105 °C)
<b>ROHS Conformity</b>	Yes
<b>Certification / Specification</b>	UL
<b>UL Listed (US and Canada)</b>	No
<b>UL Recognized (US and Canada)</b>	Yes