

T18R3-2K2



Article Number: 111-01768

Standard Cable Tie, 4" Long, 18lb Tensile Strength, PA66, Orange/Red Striped, 50/pkg

 RoHS

Base Data

Local Order Number	T18R3-2K2
Type	T18R
Color	Red (RD) Orange (OG)
Features and Benefits	• Inside serrations allow for strong hold on cables and wire bundles. • Head design provides high tensile strength with very low insertion force. • Bent tail ensures a quick and simple installation.
Product Description	HellermannTyton standard cable ties feature inside serrations providing a positive hold onto wire and cable bundles. The head design guarantees high tensile strength, as well as a low insertion force. The bent tail design allows quick and simple installations by hand. For high volume applications, tensioning tools are availableto ensure consistent and safe installation.
Fixation Method (FF)	None
Identification Plate Position	none
Releasable Closure (Yes/No)	No
Variant	Inside Serrated
Short Description	Standard Cable Tie, 4" Long, 18lb Tensile Strength, PA66, Orange/Red Striped, 50/pkg

Product Dimensions

Minimum Tensile Strength (imperial)	18.0 lbs
Minimum Tensile Strength (N)	80.0 N
Length L (imperial)	4.0 "
Length L (metric)	100.0 mm
Width W (imperial)	0.1 "
Width W (metric)	2.45 mm
Bundle Diameter min (imperial)	0.06 "
Bundle Diameter min (metric)	1.5 mm
Bundle Diameter max (imperial)	0.86 "
Bundle Diameter max (metric)	22.0 mm

Logistics and Packaging

Quantity per	bag
Package Quantity	50
Carton Quantity	10000

Material and Specifications

Material	Polyamide 6.6 (PA66)
----------	----------------------

Material Shortcut PA66

Flammability UL94 V2

Halogenfree Yes

Operating Temperature -40 °F to +185 °F (-40 °C to +85 °C)

ROHS Conformity Yes

Certification / Specification UL ZODZ2.E64139
MIL 53421

UL Listed (US and Canada) No

UL Recognized (US and Canada) No