

T18R5-2K2



Article Number: 111-01773

Standard Cable Tie, 4" Long, 18lb Tensile Strength, PA66, Green/Red Striped, 50/pkg



Base Data

Local Order Number T18R5-2K2

Type T18R

Color Green (GN)
Red (RD)

- Features and Benefits**
- Inside serrations allow for strong hold on cables and wire bundles.
 - Head design provides high tensile strength with very low insertion force.
 - Bent tail ensures a quick and simple installation.

Product Description HellermannTyton standard cable ties feature inside serrations providing a positive hold onto wire and cable bundles. The head design guarantees high tensile strength, as well as a low insertion force. The bent tail design allows quick and simple installations by hand. For high volume applications, tensioning tools are available to ensure consistent and safe installation.

Fixation Method (FF) None

Identification Plate Position none

Releasable Closure (Yes/No) No

Variant Inside Serrated

Short Description Standard Cable Tie, 4" Long, 18lb Tensile Strength, PA66, Green/Red Striped, 50/pkg

Product Dimensions

Minimum Tensile Strength (imperial) 18.0 lbs

Minimum Tensile Strength (N) 80.0 N

Length L (imperial) 4.0 "

Length L (metric) 100.0 mm

Width W (imperial) 0.1 "

Width W (metric) 2.45 mm

Bundle Diameter min (imperial) 0.06 "

Bundle Diameter min (metric) 1.5 mm

Bundle Diameter max (imperial) 0.86 "

Bundle Diameter max (metric) 22.0 mm

Logistics and Packaging

Quantity per bag

Package Quantity 50

Carton Quantity 10000

Material and Specifications

Material Polyamide 6.6 (PA66)

Material Shortcut PA66

Flammability UL94 V2

Halogenfree Yes

Operating Temperature -40 °F to +185 °F (-40 °C to +85 °C)

ROHS Conformity Yes

Certification / Specification UL ZODZ2.E64139
MIL 53421

UL Listed (US and Canada) No

UL Recognized (US and Canada) No