# HellermannTyton

# T18R9PPM4



Article Number: 111-01922

High Temp Cable Tie, 4" Long, 8lb Tensile Strength, PP, Natural, 1000/pkg

RoHS

## Base Data

Local Order Number	T18R9PPM4
Туре	T18R
Color	Natural (NA)
Features and Benefits	<ul> <li>Polypropylene cable ties provide excellent resistance to chemicals and salts.</li> <li>Inside serrations allow for strong hold on cables and wire bundles.</li> <li>Head design provides high tensile strength with very low insertion force.</li> <li>Bent tail ensures a quick and simple installation.</li> </ul>
Product Description	HellermannTyton high temperature cable ties are made of specially formulated materials providing various levels of temperature resistance and performance. The cable ties feature inside serrations providing a positive hold onto wire and cable bundles. The head design guarantees high tensile strength, as well as a low insertion force. The bent tail design allows quick and simple installations by hand. For high volume applications, tensioning tools are available to ensure consistent and safe installation.
Fixation Method (FF)	None
Identification Plate Position	none
Releasable Closure (Yes/No)	No
Tie Closure	plastic pawl
Variant	Inside Serrated
Short Description	High Temp Cable Tie, 4" Long, 8lb Tensile Strength, PP, Natural, 1000/pkg

#### **Product Dimensions**

Minimum Tensile Strength (imperial)	8.0 lbs
Minimum Tensile Strength (N)	36.0 N
Length L (imperial)	4.0 "
Length L (metric)	100.0 mm
Width W (imperial)	0.1 "
Width W (metric)	2.45 mm
Bundle Diameter min (imperial)	0.06 "
Bundle Diameter min (metric)	1.5 mm
Bundle Diameter max (imperial)	0.86 "
Bundle Diameter max (metric)	22.0 mm
Thickness T (imperial)	0.039 "
Thickness T (Metric)	1.0 mm

# Logistics and Packaging

Quantity per bag
Package Quantity 1000

Carton Quantity 10000

Weight (Metric) 0.28 kg

## **Material and Specifications**

Material	Polypropylene (PP)
Material Shortcut	PP
Flammability	UL94 HB
Halogenfree	Yes
Operating Temperature	-40 °F to +239 °F (-40 °C to +115 °C)
ROHS Conformity	Yes
UL Listed (US and Canada)	No
UL Recognized (US and Canada)	No

© HellermannTyton 2014