

T18RA5000HSW



Article Number: 120-05007

Cable Tie for AT2000, 18 lb Tensile Strength, PA66HS, Black, 5,000/reel

Base Data

Local Order Number	T18RA5000HSW
Type	T18RA5000
Color	Black (BK)
Features and Benefits	<ul style="list-style-type: none">• The AT2000 cable tie system is designed for automatic installation on bundles up to .75" and a minimum tensile strength of 18 lbs.• Available in reels of 5,000 each or bandoliers of 50 each.
Product Description	HellermannTyton offers the widest range of automatic cable tie tool systems which cover cable tie tensile strengths of 18, 30, and 50 pounds with bundle diameters between 1/16" to over 3". For use with HellermannTyton's Automatic Tool Systems.
Power Supply unit	Electrical
Tie Closure	plastic pawl
Short Description	Cable Tie for AT2000, 18 lb Tensile Strength, PA66HS, Black, 5,000/reel

Product Dimensions

Minimum Tensile Strength (imperial)	18.0 lbs
Minimum Tensile Strength (N)	80.0 N
Length L (imperial)	4.0 "
Length L (metric)	4.8 mm
Width W (imperial)	0.1 "
Width W (metric)	2.5 mm
Bundle Diameter min (imperial)	0.03 "
Bundle Diameter min (metric)	0.7 mm
Bundle Diameter max (imperial)	0.75 "
Bundle Diameter max (metric)	20.0 mm

Logistics and Packaging

Quantity per	reel
Package Quantity	5000

Material and Specifications

Material	Polyamide 6.6 heat stabilized (PA66HS)
Material Shortcut	PA66HS
Flammability	UL94 V2
Operating Temperature	-40 °F to +275 °F (-40 °C to +135 °C)
UL Listed (US and Canada)	No

UL Recognized (US and Canada) Yes

© HellemanTyton 2014