

T18RA50HSW



Article Number: 120-05003

Cable Tie for AT2000, 18 lb Tensile Strength, PA66HS, Black, 50/bandolier, 500/pkg

Base Data

Local Order Number T18RA50HSW

Type T18RA50

Color Black (BK)

Features and Benefits

- The AT2000 cable tie system is designed for automatic installation on bundles up to .75" and a minimum tensile strength of 18 lbs.
- Available in reels of 5,000 each or bandoliers of 50 each.

Product Description HellermannTyton offers the widest range of automatic cable tie tool systems which cover cable tie tensile strengths of 18, 30, and 50 pounds with bundle diameters between 1/16" to over 3". For use with HellermannTyton's Automatic Tool Systems.

Power Supply unit Electrical

Tie Closure plastic pawl

Short Description Cable Tie for AT2000, 18 lb Tensile Strength, PA66HS, Black, 50/bandolier, 500/pkg

Product Dimensions

Minimum Tensile Strength (imperial) 18.0 lbs

Minimum Tensile Strength (N) 80.0 N

Length L (imperial) 4.0 "

Length L (metric) 4.8 mm

Width W (imperial) 0.1 "

Width W (metric) 2.5 mm

Bundle Diameter min (imperial) 0.03 "

Bundle Diameter min (metric) 0.7 mm

Bundle Diameter max (imperial) 0.75 "

Bundle Diameter max (metric) 20.0 mm

Logistics and Packaging

Quantity per bag

Package Quantity 500

Material and Specifications

Material Polyamide 6.6 heat stabilized (PA66HS)

Material Shortcut PA66HS

Flammability UL94 V2

Halogenfree Yes

Operating Temperature -40 °F to +257 °F (-40 °C to +125 °C)

UL Listed (US and Canada) No

UL Recognized (US and Canada) Yes