

T18S0C2

Article Number: 111-02810

Standard Cable Tie, 3.3" Long, 18lb Tensile Strength, PA66, Black, 100/pkg



Base Data

Local Order Number T18S0C2

Type T18S

Color Black (BK)

- Features and Benefits**
- Inside serrations allow for strong hold on cables and wire bundles.
 - Head design provides high tensile strength with very low insertion force.
 - Bent tail ensures a quick and simple installation.

Product Description HellermannTyton standard cable ties feature inside serrations providing a positive hold onto wire and cable bundles. The head design guarantees high tensile strength, as well as a low insertion force. The bent tail design allows quick and simple installations by hand. For high volume applications, tensioning tools are available to ensure consistent and safe installation.

Fixation Method (FF) None

Identification Plate Position none

Releasable Closure (Yes/No) No

Tie Closure plastic pawl

Variant Inside Serrated

Short Description Standard Cable Tie, 3.3" Long, 18lb Tensile Strength, PA66, Black, 100/pkg

Product Dimensions

Minimum Tensile Strength (imperial) 18.0 lbs

Minimum Tensile Strength (N) 80 N

Length L (imperial) 3.27 "

Length L (metric) 83.0 mm

Width W (imperial) 0.09 "

Width W (metric) 2.3 mm

Bundle Diameter min (imperial) 0.06 "

Bundle Diameter min (metric) 1.5 mm

Bundle Diameter max (imperial) 0.63 "

Bundle Diameter max (metric) 16.0 mm

Cable Tie Head Height (Metric) 3.2 mm

Cable Tie Head Length (metric) 4.2 mm

Cable Tie Head Width (metric) 4.5 mm

Cable Tie Head Length (imperial) 0.17 "

Cable Tie Head Width (imperial) 0.18 "

Logistics and Packaging

Quantity per bag

Package Quantity 100

Carton Quantity 40000

Material and Specifications

Material Polyamide 6.6 (PA66)

Material Shortcut PA66

Flammability UL94 V2

Halogenfree Yes

Operating Temperature -40 °F to +185 °F (-40 °C to +85 °C)

ROHS Conformity Yes

Certification / Specification UL ZODZ2.E85319

UL Listed (US and Canada) Yes

UL Recognized (US and Canada) Yes