

T250R0HIRUVX2

Article Number: 111-24805

Heavy Duty Cable Tie, 20.3" Long, 250 lb Tensile Strength, PA66HIRHSUV, Black, 25/pkg



Base Data

Local Order Number	T250R0HIRUVX2
Type	T250R
Color	Black (BK)
Features and Benefits	• High impact, heat and UV stabilized heavy duty cable ties contain an impact modifier allowing greater flexibility and greater resistance to vibration. • Heavy duty design to offer higher tensile strength. • Buckle feature on head allows excess strap to be tucked away after installation.
Product Description	HellermannTyton heavy duty cable ties offer a higher tensile strength for heavy load applications. The head design guarantees high tensile strength, as well as a low insertion force. For high volume applications, tensioning tools are available to ensure consistent and safe installation.
Fixation Method (FF)	None
Identification Plate Position	none
Releasable Closure (Yes/No)	No
Tie Closure	plastic pawl
Variant	Inside Serrated
Short Description	Heavy Duty Cable Tie, 20.3" Long, 250 lb Tensile Strength, PA66HIRHSUV, Black, 25/pkg

Product Dimensions

Minimum Tensile Strength (imperial)	250.0 lbs
Minimum Tensile Strength (N)	1115.0 N
Length L (imperial)	20.3 "
Length L (metric)	515.0 mm
Width W (imperial)	0.49 "
Width W (metric)	12.5 mm
Bundle Diameter min (imperial)	0.47 "
Bundle Diameter min (metric)	12.0 mm
Bundle Diameter max (imperial)	4.9 "
Bundle Diameter max (metric)	125.0 mm
Thickness T (imperial)	0.075 "
Thickness T (Metric)	1.9 mm

Logistics and Packaging

Quantity per	bag
Package Quantity	25
Carton Quantity	500 Pieces
Weight (Metric)	16.33 kg

Material and Specifications

Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	PA66HIRHSUV
Flammability	UL94 HB
Halogenfree	Yes
Operating Temperature	-40 °F to +230 °F (-40 °C to +110 °C)
ROHS Conformity	Yes
Certification / Specification	UL ZODZ2.E64139
UL Listed (US and Canada)	No
UL Recognized (US and Canada)	No