

## T250R0X2



**Article Number:** 111-24801

**Heavy Duty Cable Tie, 20.3" Long, 250 lb Tensile Strength, PA66, Black, 25/pkg**



### Base Data

**Local Order Number** T250R0X2

**Type** T250R

**Color** Black (BK)

- Features and Benefits**
- Heavy duty design to offer higher tensile strength.
  - Buckle feature on head allows excess strap to be tucked away after installation.

**Product Description** HellermannTyton heavy duty cable ties offer a higher tensile strength for heavy load applications. The head design guarantees high tensile strength, as well as a low insertion force. For high volume applications, tensioning tools are available to ensure consistent and safe installation.

**Fixation Method (FF)** None

**Identification Plate Position** none

**Releasable Closure (Yes/No)** No

**Tie Closure** plastic pawl

**Variant** Inside Serrated

**Short Description** Heavy Duty Cable Tie, 20.3" Long, 250 lb Tensile Strength, PA66, Black, 25/pkg

### Product Dimensions

**Minimum Tensile Strength (imperial)** 250.0 lbs

**Minimum Tensile Strength (N)** 1115.0 N

**Length L (imperial)** 20.3 "

**Length L (metric)** 515.0 mm

**Width W (imperial)** 0.49 "

**Width W (metric)** 12.5 mm

**Bundle Diameter min (imperial)** 0.47 "

**Bundle Diameter min (metric)** 12.0 mm

**Bundle Diameter max (imperial)** 4.9 "

**Bundle Diameter max (metric)** 125.0 mm

### Logistics and Packaging

**Quantity per** bag

**Package Quantity** 25

**Carton Quantity** 500

### Material and Specifications

**Material** Polyamide 6.6 (PA66)

**Material Shortcut** PA66

**CSA Certified** No  
**Flammability** UL94 V2  
**Halogenfree** Yes  
**Operating Temperature** -40 °F to +185 °F (-40 °C to +85 °C)  
**ROHS Conformity** Yes  
**Certification / Specification** UL ZODZ2.E64139  
**UL Listed (US and Canada)** No  
**UL Recognized (US and Canada)** Yes