

T250S0X2



Article Number: 111-24700

Heavy Duty Cable Tie, 9.1" Long, 250 lb Tensile Strength, PA66, Black, 25/pkg

 **RoHS**

Base Data

Local Order Number	T250S0X2
Type	T250S
Color	Black (BK)
Features and Benefits	• Heavy duty design to offer higher tensile strength. • Buckle feature on head allows excess strap to be tucked away after installation.
Product Description	HellermannTyton heavy duty cable ties offer a higher tensile strength for heavy load applications. The head design guarantees high tensile strength, as well as a low insertion force. For high volume applications, tensioning tools are available to ensure consistent and safe installation.
Fixation Method (FF)	None
Identification Plate Position	none
Releasable Closure (Yes/No)	No
Variant	Inside Serrated
Short Description	Heavy Duty Cable Tie, 9.1" Long, 250 lb Tensile Strength, PA66, Black, 25/pkg

Product Dimensions

Minimum Tensile Strength (imperial)	250.0 lbs
Minimum Tensile Strength (N)	1115.0 N
Length L (imperial)	9.1 "
Length L (metric)	230.0 mm
Width W (imperial)	0.49 "
Width W (metric)	12.5 mm
Bundle Diameter min (imperial)	0.47 "
Bundle Diameter min (metric)	12.0 mm
Bundle Diameter max (imperial)	2.0 "
Bundle Diameter max (metric)	50.0 mm

Logistics and Packaging

Quantity per	bag
Package Quantity	25
Carton Quantity	1000

Material and Specifications

Material	Polyamide 6.6 (PA66)
Material Shortcut	PA66
CSA Certified	No

Flammability	UL94 V2
Halogenfree	Yes
Operating Temperature	-40 °F to +185 °F (-40 °C to +85 °C)
ROHS Conformity	Yes
Certification / Specification	UL ZODZ2.E64139
UL Listed (US and Canada)	No
UL Recognized (US and Canada)	Yes