

## T255S0HIRX2



**Article Number:** 111-25500

**Heavy Duty Cable Tie, 8.9" Long, 250 lb Tensile Strength, PA66HIRHSUV, Black, 25/pkg**



### Base Data

**Local Order Number** T255S0HIRX2

**Type** T255S

**Color** Black (BK)

**Features and Benefits**

- High impact, heat and UV stabilized heavy duty cable ties contain an impact modifier allowing greater flexibility and greater resistance to vibration.
- Head design provides high tensile strength with very low insertion force.
- Bent tail ensures a quick and simple installation.

**Product Description** HellermannTyton heavy duty cable ties offer a higher tensile strength for heavy load applications. The head design guarantees high tensile strength, as well as a low insertion force. For high volume applications, tensioning tools are available to ensure consistent and safe installation.

**Fixation Method (FF)** None

**Identification Plate Position** none

**Releasable Closure (Yes/No)** No

**Variant** Inside Serrated

**Short Description** Heavy Duty Cable Tie, 8.9" Long, 250 lb Tensile Strength, PA66HIRHSUV, Black, 25/pkg

### Product Dimensions

**Minimum Tensile Strength (imperial)** 250.0 lbs

**Minimum Tensile Strength (N)** 1115.0 N

**Length L (imperial)** 8.9 "

**Length L (metric)** 225.0 mm

**Width W (imperial)** 0.5 "

**Width W (metric)** 12.6 mm

**Bundle Diameter min (imperial)** 0.49 "

**Bundle Diameter min (metric)** 12.5 mm

**Bundle Diameter max (imperial)** 2.2 "

**Bundle Diameter max (metric)** 55.0 mm

### Logistics and Packaging

**Quantity per** bag

**Package Quantity** 25

**Carton Quantity** 1000

### Material and Specifications

**Material** Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)

**Material Shortcut** PA66HIRHSUV

**CSA Certified** No

**Flammability** UL94 HB

**Operating Temperature** -40 °F to +230 °F (-40 °C to +110 °C)

**ROHS Conformity** Yes

**UL Listed (US and Canada)** No

**UL Recognized (US and Canada)** No