

## T30RA3000



**Article Number:** 103-00001

**Cable Tie for AT2060, 30 lb Tensile Strength, PA66, Natural, 3000/reel**

### Base Data

**Local Order Number** T30RA3000

**Type** IT30RA

**Color** Natural (NA)

**Features and Benefits**

- The AT2060 cable tie system is designed for automatic installation on bundles up to 1.25" and a minimum tensile strength of 30 lbs.
- Available in reels of 3,000 each or bandoliers of 30 each.

**Product Description** HellermannTyton offers the widest range of automatic cable tie tool systems which cover cable tie tensile strengths of 18, 30, and 50 pounds with bundle diameters between 1/16" to over 3". For use with HellermannTyton's Automatic Tool Systems.

**Identification Plate Position** none

**Releasable Closure (Yes/No)** No

**Voltage range** 27 Volt

**Short Description** Cable Tie for AT2060, 30 lb Tensile Strength, PA66, Natural, 3000/reel

### Product Dimensions

**Minimum Tensile Strength (imperial)** 30.0 lbs

**Minimum Tensile Strength (N)** 135.0 N

**Length L (imperial)** 6.0 "

**Length L (metric)** 152.0 mm

**Cycle Time** 1.2 seconds

**Width W (imperial)** 0.14 "

**Width W (metric)** 3.6 mm

**Bundle Diameter min (imperial)** 0.06 "

**Bundle Diameter min (metric)** 1.5 mm

**Bundle Diameter max (imperial)** 1.25 "

**Bundle Diameter max (metric)** 31.0 mm

**Thickness T (imperial)** 0.05 "

**Power Supply** Electrical

**Tension Force** Adjustable

**Thickness T (Metric)** 1.2 mm

### Logistics and Packaging

**Quantity per** reel

**Package Quantity (imperial)** 2

**Package Quantity** 3000

<b>Carton Quantity</b>	6000
<b>Reel Diameter (imperial)</b>	17.7 "
<b>Reel Diameter (metric)</b>	450 mm
<b>Reel Weight (imperial)</b>	7 lbs
<b>Reel Weight (metric)</b>	3.175 kg
<b>Reel Width (imperial)</b>	7.197 "
<b>Reel Width (metric)</b>	182.8 m
<b>Weight (imperial)</b>	3.9 lbs

---

## Material and Specifications

<b>Material</b>	Polyamide 6.6 (PA66)
<b>Material Shortcut</b>	PA66
<b>US MILSPEC</b>	MS3367-5-9
<b>Flammability</b>	UL94 V2
<b>Operating Temperature</b>	-40 °F to +185 °F (-40 °C to +85 °C)
<b>UL Listed (US and Canada)</b>	No
<b>UL Recognized (US and Canada)</b>	Yes