

T30RA300HS



Article Number: 103-00003

Cable Tie for AT2060, 30 lb Tensile Strength, PA66HS, Black, 30/bandolier, 600/pkg

Base Data

Local Order Number T30RA300HS

Type T30RA

Color Black (BK)

Features and Benefits

- The AT2060 cable tie system is designed for automatic installation on bundles up to 1.25" and a minimum tensile strength of 30 lbs.
- Available in reels of 3,000 each or bandoliers of 30 each.

Product Description HellermannTyton offers the widest range of automatic cable tie tool systems which cover cable tie tensile strengths of 18, 30, and 50 pounds with bundle diameters between 1/16" to over 3". For use with HellermannTyton's Automatic Tool Systems.

Identification Plate Position none

Releasable Closure (Yes/No) No

Voltage range 27 Volt

Short Description Cable Tie for AT2060, 30 lb Tensile Strength, PA66HS, Black, 30/bandolier, 600/pkg

Product Dimensions

Minimum Tensile Strength (imperial) 30.0 lbs

Minimum Tensile Strength (N) 135.0 N

Length L (imperial) 6.0 "

Length L (metric) 152.0 mm

Cycle Time 1.2 seconds

Width W (imperial) 0.14 "

Width W (metric) 3.6 mm

Bundle Diameter min (imperial) 0.06 "

Bundle Diameter min (metric) 1.5 mm

Bundle Diameter max (imperial) 1.25 "

Bundle Diameter max (metric) 31.0 mm

Thickness T (imperial) 0.05 "

Power Supply Electrical

Tension Force Adjustable

Thickness T (Metric) 1.2 mm

Logistics and Packaging

Quantity per bag

Package Quantity 600

Carton Quantity 6000

Reel Diameter (imperial)	17.7 "
Reel Diameter (metric)	450 mm
Reel Weight (imperial)	7 lbs
Reel Weight (metric)	3.175 kg
Reel Width (imperial)	7.197 "
Reel Width (metric)	182.8 m
Weight (imperial)	3.9 lbs

Material and Specifications

Material	Polyamide 6.6 heat stabilized (PA66HS)
Material Shortcut	PA66HS
Flammability	UL94 V2
Operating Temperature	-40 °F to +275 °F (-40 °C to +135 °C)
UL Listed (US and Canada)	No
UL Recognized (US and Canada)	Yes