

T30RSF0C2

Article Number: 126-00700

Push Mount Tie, 6.3" Long, 30lb Tensile, Panel Thickness 0.19"- 0.22", PA66HS, Black, 100/pkg



Base Data

Local Order Number	T30RSF0C2
Type	T30RSF(U)
Color	Black (BK)
Features and Benefits	<ul style="list-style-type: none"> • Push Mount design provides quick and easy mounting. • Push mount style creates low insertion and high extraction force. • Ties "clicks" into place upon final installation signaling installer insertion is complete.
Product Description	Push Mount Ties provide a one piece, all plastic tie for quick and simple cable mounting.
Fixation Method (FF)	Arrowhead
Identification Plate Position	none
Releasable Closure (Yes/No)	No
Tie Closure	plastic pawl
Variant	Inside Serrated
Short Description	Push Mount Tie, 6.3" Long, 30lb Tensile, Panel Thickness 0.19"- 0.22", PA66HS, Black, 100/pkg

Product Dimensions

Minimum Tensile Strength (imperial)	30.0 lbs
Minimum Tensile Strength (N)	135 N
Length L (imperial)	6.3 "
Length L (metric)	161.0 mm
Width W (imperial)	0.14 "
Width W (metric)	3.6 mm
Height H (imperial)	0.2 "
Height H (metric)	5.7 mm
Bundle Diameter min (imperial)	0.06 "
Bundle Diameter min (metric)	1.6 mm
Bundle Diameter max (imperial)	1.3 "
Bundle Diameter max (metric)	31.0 mm
Panel Thickness max. (imperial)	0.09 "
Panel Thickness max. (metric)	2.4 mm
Panel Thickness min. (imperial)	0.04 "
Panel Thickness min. (metric)	0.9 mm
Mounting Hole Diameter D (imperial)	0.19 - 0.22 "
Mounting Hole Diameter D (metric)	4.7 - 5.5 mm
Mounting Hole Diameter D min (imperial)	0.19 "

Mounting Hole Diameter D max 0.22 "
(imperial)

Thickness T (imperial) 0.05 "

Mounting Hole Diameter D max (metric) 5.6 mm

Mounting Hole Diameter D min (metric) 4.8 mm

Thickness T (Metric) 1.2 mm

Logistics and Packaging

Quantity per bag

Package Quantity 100

Carton Quantity 5000

Material and Specifications

Material Polyamide 6.6 heat stabilized (PA66HS)

Material Shortcut PA66HS

CSA Certified No

Flammability UL94 V2

Operating Temperature -40 °F to +221 °F (-40 °C to +105 °C)

ROHS Conformity Yes

Certification / Specification UL

UL Listed (US and Canada) No

UL Recognized (US and Canada) Yes