

T30RSF0M4



Article Number: 126-00702

Push Mount Tie, 6.3" Long, 30lb Tensile, Panel Thickness 0.19"- 0.22", PA66HS, Black, 1,000/pkg

 RoHS

Base Data

|                               |                                                                                                                                                                                                                                                                                         |
|-------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Local Order Number            | T30RSF0M4                                                                                                                                                                                                                                                                               |
| Type                          | T30RSF(U)                                                                                                                                                                                                                                                                               |
| Color                         | Black (BK)                                                                                                                                                                                                                                                                              |
| Features and Benefits         | <ul style="list-style-type: none"><li>• Push Mount design provides quick and easy mounting.</li><li>• Push mount style creates low insertion and high extraction force.</li><li>• Ties "clicks" into place upon final installation signaling installer insertion is complete.</li></ul> |
| Product Description           | Push Mount Ties provide a one piece, all plastic tie for quick and simple cable mounting.                                                                                                                                                                                               |
| Fixation Method (FF)          | Arrowhead                                                                                                                                                                                                                                                                               |
| Identification Plate Position | none                                                                                                                                                                                                                                                                                    |
| Releasable Closure (Yes/No)   | No                                                                                                                                                                                                                                                                                      |
| Tie Closure                   | plastic pawl                                                                                                                                                                                                                                                                            |
| Variant                       | Inside Serrated                                                                                                                                                                                                                                                                         |
| Short Description             | Push Mount Tie, 6.3" Long, 30lb Tensile, Panel Thickness 0.19"- 0.22", PA66HS, Black, 1,000/pkg                                                                                                                                                                                         |

Product Dimensions

|                                         |               |
|-----------------------------------------|---------------|
| Minimum Tensile Strength (imperial)     | 30.0 lbs      |
| Minimum Tensile Strength (N)            | 135 N         |
| Length L (imperial)                     | 6.3 "         |
| Length L (metric)                       | 161.0 mm      |
| Width W (imperial)                      | 0.14 "        |
| Width W (metric)                        | 3.6 mm        |
| Height H (imperial)                     | 0.2 "         |
| Height H (metric)                       | 5.7 mm        |
| Bundle Diameter min (imperial)          | 0.06 "        |
| Bundle Diameter min (metric)            | 1.6 mm        |
| Bundle Diameter max (imperial)          | 1.3 "         |
| Bundle Diameter max (metric)            | 31.0 mm       |
| Panel Thickness max. (imperial)         | 0.09 "        |
| Panel Thickness max. (metric)           | 2.4 mm        |
| Panel Thickness min. (imperial)         | 0.04 "        |
| Panel Thickness min. (metric)           | 0.9 mm        |
| Mounting Hole Diameter D (imperial)     | 0.19 - 0.22 " |
| Mounting Hole Diameter D (metric)       | 4.7 - 5.5 mm  |
| Mounting Hole Diameter D min (imperial) | 0.19 "        |

Mounting Hole Diameter D max 0.22 "  
(imperial)

Thickness T (imperial) 0.05 "

Mounting Hole Diameter D max 5.6 mm  
(metric)

Mounting Hole Diameter D min (metric) 4.8 mm

Thickness T (Metric) 1.2 mm

## Logistics and Packaging

---

Quantity per bag

Package Quantity 1000

Carton Quantity 5000

## Material and Specifications

---

Material Polyamide 6.6 heat stabilized (PA66HS)

Material Shortcut PA66HS

CSA Certified No

Flammability UL94 V2

Operating Temperature -40 °F to +221 °F (-40 °C to +105 °C)

ROHS Conformity Yes

Certification / Specification UL

UL Listed (US and Canada) No

UL Recognized (US and Canada) Yes