

T30RSF9C2

Article Number: 111-85603

Push Mount Tie, 6.3" Long, 30lb Tensile, Panel Thickness 0.19"- 0.22", PA66, Natural, 100/pkg



Base Data

Local Order Number	T30RSF9C2
Type	T30RSF(U)
Color	Natural (NA)
Features and Benefits	<ul style="list-style-type: none"> • Push Mount design provides quick and easy mounting. • Push mount style creates low insertion and high extraction force. • Ties "clicks" into place upon final installation signaling installer insertion is complete.
Product Description	Push Mount Ties provide a one piece, all plastic tie for quick and simple cable mounting.
Fixation Method (FF)	Arrowhead
Identification Plate Position	none
Releasable Closure (Yes/No)	No
Tie Closure	plastic pawl
Variant	Inside Serrated
Short Description	Push Mount Tie, 6.3" Long, 30lb Tensile, Panel Thickness 0.19"- 0.22", PA66, Natural, 100/pkg

Product Dimensions

Minimum Tensile Strength (imperial)	30.0 lbs
Minimum Tensile Strength (N)	136 N
Length L (imperial)	6.3 "
Length L (metric)	158.0 mm
Width W (imperial)	0.14 "
Width W (metric)	3.6 mm
Height H (imperial)	0.2 "
Height H (metric)	5.8 mm
Bundle Diameter min (imperial)	0.06 "
Bundle Diameter min (metric)	1.6 mm
Bundle Diameter max (imperial)	1.3 "
Bundle Diameter max (metric)	32.0 mm
Panel Thickness max. (imperial)	0.09 "
Panel Thickness max. (metric)	2.1 mm
Panel Thickness min. (imperial)	0.04 "
Panel Thickness min. (metric)	0.75 mm
Mounting Hole Diameter D (imperial)	0.19 - 0.22 "
Mounting Hole Diameter D (metric)	4.7 - 5.5 mm
Mounting Hole Diameter D min (imperial)	0.19 "

Mounting Hole Diameter D max 0.22 "
(imperial)

Thickness T (imperial) 0.05 "

Mounting Hole Diameter D max (metric) 5.6 mm

Mounting Hole Diameter D min (metric) 4.7 mm

Thickness T (Metric) 1.2 mm

Logistics and Packaging

Quantity per bag
Package Quantity 100
Carton Quantity 5000 Pieces
Weight (Metric) 0.9 kg

Material and Specifications

Material Polyamide 6.6 (PA66)
Material Shortcut PA66
CSA Certified No
Flammability UL94 V2
Operating Temperature -40 °F to +185 °F (-40 °C to +85 °C)
ROHS Conformity Yes
Certification / Specification UL
UL Listed (US and Canada) No
UL Recognized (US and Canada) Yes