

T30RSF9M4

Article Number: 126-00704

Push Mount Tie, 6.3" Long, 30lb Tensile, Panel Thickness 0.19"- 0.22", PA66, Natural, 1,000/pkg



Base Data

Local Order Number	T30RSF9M4
Type	T30RSF(U)
Color	Natural (NA)
Features and Benefits	<ul style="list-style-type: none"> • Push Mount design provides quick and easy mounting. • Push mount style creates low insertion and high extraction force. • Ties "clicks" into place upon final installation signaling installer insertion is complete.
Product Description	Push Mount Ties provide a one piece, all plastic tie for quick and simple cable mounting.
Fixation Method (FF)	Arrowhead
Identification Plate Position	none
Releasable Closure (Yes/No)	No
Tie Closure	plastic pawl
Variant	Inside Serrated
Short Description	Push Mount Tie, 6.3" Long, 30lb Tensile, Panel Thickness 0.19"- 0.22", PA66, Natural, 1,000/pkg

Product Dimensions

Minimum Tensile Strength (imperial)	30.0 lbs
Minimum Tensile Strength (N)	135 N
Length L (imperial)	6.3 "
Length L (metric)	161.0 mm
Width W (imperial)	0.14 "
Width W (metric)	3.6 mm
Height H (imperial)	0.2 "
Height H (metric)	5.7 mm
Bundle Diameter min (imperial)	0.06 "
Bundle Diameter min (metric)	1.6 mm
Bundle Diameter max (imperial)	1.3 "
Bundle Diameter max (metric)	31.0 mm
Panel Thickness max. (imperial)	0.09 "
Panel Thickness max. (metric)	2.4 mm
Panel Thickness min. (imperial)	0.04 "
Panel Thickness min. (metric)	0.9 mm
Mounting Hole Diameter D (imperial)	0.19 - 0.22 "
Mounting Hole Diameter D (metric)	4.7 - 5.5 mm
Mounting Hole Diameter D min (imperial)	0.19 "

Mounting Hole Diameter D max 0.22 "
(imperial)

Thickness T (imperial) 0.05 "

Mounting Hole Diameter D max 5.6 mm
(metric)

Mounting Hole Diameter D min (metric) 4.8 mm

Thickness T (Metric) 1.2 mm

Logistics and Packaging

Quantity per bag

Package Quantity 1000

Carton Quantity 5000

Material and Specifications

Material Polyamide 6.6 (PA66)

Material Shortcut PA66

CSA Certified No

Flammability UL94 V2

Operating Temperature -40 °F to +185 °F (-40 °C to +85 °C)

ROHS Conformity Yes

Certification / Specification UL

UL Listed (US and Canada) No

UL Recognized (US and Canada) Yes