# HellermannTyton

# T3D043710M4



Article Number: 211-00140

P Clamp, .375" Width, .438" Max Bundle Dia, .203" Mounting Hole Dia, PA66, White, 1000/pkg

RoHS

# Base Data

| Local Order Number    | T3D043710M4   |
|-----------------------|---|
| Туре                  | T3D0437   |
| Color                 | White (WH)  |
| Features and Benefits | <ul> <li>P-Clamps easily guide and locate wire and cables up to 0.625" in diameter.</li> <li>Designed with a radiused edge to prevent chaffing and cutting into insulation.</li> </ul>                      |
| Product Description   | HellermannTyton P Clamps easily guide and locate wires and cables. The clamps are designed with a radiused edge to prevent chaffing and cutting into insulation. Available sizes up to 1" bundle diameters. |
| Fixation Method (FF)  | screw-hole  |
| Variant               | Closed  |
| Short Description     | P Clamp, .375" Width, .438" Max Bundle Dia, .203" Mounting Hole Dia, PA66, White, 1000/pkg  |

#### **Product Dimensions**

| Width W (imperial)                  | 0.375 "  |
|-------------------------------------|----------|
| Width W (metric)                    | 9.53 mm  |
| Bundle Diameter max (imperial)      | 0.438 "  |
| Bundle Diameter max (metric)        | 11.13 mm |
| Mounting Hole Diameter D (imperial) | 0.203 "  |
| Mounting Hole Diameter D (metric)   | 5.1 mm   |
| Wall Thickness WT (imperial)        | .050 "   |
| Wall Thickness WT (metric)          | 1.3 mm   |
| Mounting Hole Centers (imperial)    | 0.574 "  |
| Mounting Hole Centers (metric)      | 14.6 mm  |
|                                     |          |

## Logistics and Packaging

| Quantity pe | <b>r</b> bag |
|-------------|--------------|
|             |              |

| Package Quantity 1000 Pieces | <b>Nuantity</b> 1000 Pieces |
|------------------------------|-----------------------------|
|------------------------------|-----------------------------|

## **Material and Specifications**

| Material                      | Polyamide 6.6 (PA66)                 |
|-------------------------------|--------------------------------------|
| Material Shortcut             | PA66                                 |
| Flammability                  | UL94 V2                              |
| Operating Temperature         | -40 °F to +185 °F (-40 °C to +85 °C) |
| ROHS Conformity               | Yes                                  |
| UL Recognized (US and Canada) | Yes                                  |

© HellermannTyton 2014