HellermannTyton

T3D050010M4



Article Number: 211-00141

P Clamp, .375" Width, .5" Max Bundle Dia, .203" Mounting Hole Dia, PA66, White, 1000/pkg

RoHS

Base Data

Local Order Number	T3D050010M4
Туре	T3D0500
Color	White (WH)
Features and Benefits	 P-Clamps easily guide and locate wire and cables up to 0.625" in diameter. Designed with a radiused edge to prevent chaffing and cutting into insulation.
Product Description	HellermannTyton P Clamps easily guide and locate wires and cables. The clamps are designed with a radiused edge to prevent chaffing and cutting into insulation. Available sizes up to 1" bundle diameters.
Fixation Method (FF)	screw-hole
Variant	Closed
Short Description	P Clamp, .375" Width, .5" Max Bundle Dia, .203" Mounting Hole Dia, PA66, White, 1000/pkg

Product Dimensions

Width W (imperial)	0.375 "
Width W (metric)	9.53 mm
Bundle Diameter max (imperial)	0.5 "
Bundle Diameter max (metric)	12.7 mm
Mounting Hole Diameter D (imperial)	0.203 "
Mounting Hole Diameter D (metric)	5.1 mm
Wall Thickness WT (imperial)	.050 "
Wall Thickness WT (metric)	1.3 mm
Mounting Hole Centers (imperial)	0.605 "
Mounting Hole Centers (metric)	15.4 mm

Logistics and Packaging

Quantity	per	bag

Material and Specifications

Material	Polyamide 6.6 (PA66)
Material Shortcut	PA66
Flammability	UL94 V2
Operating Temperature	-40 °F to +185 °F (-40 °C to +85 °C)
ROHS Conformity	Yes
UL Recognized (US and Canada)	Yes

© HellermannTyton 2014