HellermannTyton

T3D056210M4



Article Number: 211-00143

P Clamp, .375" Width, .563" Max Bundle Dia, .203" Mounting Hole Dia, PA66, White, 1000/pkg

RoHS

Base Data

Local Order Number T3D056210M4

Type T3D0562

Color White (WH)

Features and Benefits • P-Clamps easily guide and locate wire and cables up to 0.625" in diameter.

• Designed with a radiused edge to prevent chaffing and cutting into insulation.

Product Description HellermannTyton P Clamps easily guide and locate wires and cables. The clamps are designed with a radiused edge

to prevent chaffing and cutting into insulation. Available sizes up to 1" bundle diameters.

Fixation Method (FF) screw-hole

Variant Closed

Short Description P Clamp, .375" Width, .563" Max Bundle Dia, .203" Mounting Hole Dia, PA66, White, 1000/pkg

Product Dimensions

Width W (imperial) 0.375 "

Width W (metric) 9.53 mm

Bundle Diameter max (imperial) 0.563 "

Bundle Diameter max (metric) 14.3 mm

Mounting Hole Diameter D (imperial) 0.203 "

Mounting Hole Diameter D (metric) 5.1 mm

Wall Thickness WT (imperial) .050 "

Wall Thickness WT (metric) 1.3 mm

Mounting Hole Centers (imperial) 0.606 "

Mounting Hole Centers (metric) 15.4 mm

Logistics and Packaging

Quantity per bag

Package Quantity 1000 Pieces

Material and Specifications

Material Polyamide 6.6 (PA66)

Material Shortcut PA66

Flammability UL94 V2

Operating Temperature -40 °F to +185 °F (-40 °C to +85 °C)

ROHS Conformity Yes

UL Recognized (US and Canada) Yes

