

T50ML9C2



Article Number: 113-05419

Screw Mount Tie, 50lb, 15.4", Max Bundle Diameter 4.0", #10 Screw, PA66HS, Natural, 100/pkg



Base Data

Local Order Number T50ML9C2

Type T50ML

Color Natural (NA)

Features and Benefits

- Mount design secures firmly with any #10 Screw.
- Screw mount style creates low insertion and high extraction force.

Product Description Screw Mount Cable Ties are made of all plastic and provide a quick and simple method of mounting.

Fixation Method (FF) fixing hole

Identification Plate Position none

Mounting Screw Type M5

Releasable Closure (Yes/No) No

Tie Closure plastic pawl

Variant Inside Serrated

Short Description Screw Mount Tie, 50lb, 15.4", Max Bundle Diameter 4.0", #10 Screw, PA66HS, Natural, 100/pkg

Product Dimensions

Minimum Tensile Strength (imperial) 50.0 lbs

Minimum Tensile Strength (N) 225 N

Length L (imperial) 15.4 "

Length L (metric) 390.0 mm

Width W (imperial) 0.18 "

Width W (metric) 4.7 mm

Height H (imperial) 0.23 "

Height H (metric) 5.7 mm

Bundle Diameter min (imperial) 0.12 "

Bundle Diameter min (metric) 3.0 mm

Bundle Diameter max (imperial) 4.0 "

Bundle Diameter max (metric) 100.0 mm

Mounting Hole Diameter D (imperial) 0.22 "

Mounting Hole Diameter D (metric) 5.5 mm

Thickness T (imperial) 0.05 "

Cable Tie Head Height (Metric) 5.7 mm

Cable Tie Head Length (metric) 20 mm

Cable Tie Head Width (metric) 9 mm

Cable Tie Head Length (imperial) 0.79 "

Cable Tie Head Width (imperial) 0.35 "
Thickness T (Metric) 1.2 mm

Logistics and Packaging

Quantity per bag
Package Quantity 100
Carton Quantity 5000
Weight (Metric) 2.9 kg

Material and Specifications

Material Polyamide 6.6 (PA66)
Material Shortcut PA66
CSA Certified No
Flammability UL94 V2
Operating Temperature -40 °F to +221 °F (-40 °C to +105 °C)
ROHS Conformity Yes
Certification / Specification UL
UL Listed (US and Canada) Yes
UL Recognized (US and Canada) Yes