

T50MR0HSM4



Article Number: 113-05013

Screw Mount Tie, 50 lb 8.5" Max Bundle Diameter 1.8", #10 Screw, PA66, Natural, 1,000/pkg



Base Data

Local Order Number T50MR0HSM4

Type T50MR

Color Black (BK)

Features and Benefits

- Mount design secures firmly with any #10 Screw.
- Screw mount style creates low insertion and high extraction force.

Product Description Screw Mount Cable Ties are made of all plastic and provide a quick and simple method of mounting.

Fixation Method (FF) fixing hole

Identification Plate Position none

Releasable Closure (Yes/No) No

Tie Closure plastic pawl

Variant Inside Serrated

Short Description Screw Mount Tie, 50 lb 8.5" Max Bundle Diameter 1.8", #10 Screw, PA66, Natural, 1,000/pkg

Product Dimensions

Minimum Tensile Strength (imperial) 50.0 lbs

Minimum Tensile Strength (N) 225 N

Length L (imperial) 8.5 "

Length L (metric) 215.0 mm

Width W (imperial) 0.18 "

Width W (metric) 4.7 mm

Height H (imperial) 0.22 "

Height H (metric) 5.5 mm

Bundle Diameter min (imperial) 0.06 "

Bundle Diameter min (metric) 1.5 mm

Bundle Diameter max (imperial) 1.8 "

Bundle Diameter max (metric) 45.0 mm

Mounting Hole Diameter D (imperial) 0.21 "

Mounting Hole Diameter D (metric) 5.4 mm

Thickness T (imperial) 0.05 "

Thickness T (Metric) 1.2 mm

Logistics and Packaging

Quantity per bag

Package Quantity 1000

Carton Quantity 5000

Material and Specifications

| | |
|--------------------------------------|---------------------------------------|
| Material | Polyamide 6.6 (PA66) |
| Material Shortcut | PA66 |
| CSA Certified | No |
| Flammability | UL94 V2 |
| Operating Temperature | -40 °F to +221 °F (-40 °C to +105 °C) |
| ROHS Conformity | Yes |
| Certification / Specification | UL |
| UL Listed (US and Canada) | No |
| UL Recognized (US and Canada) | Yes |