

## T50R0PPC2



**Article Number:** 111-04928

**High Temp Tie, 8" Long, 25lb Tensile Strength, PP, Black, 100/pkg**



### Base Data

**Local Order Number** T50R0PPC2

**Type** T50R

**Color** Black (BK)

- Features and Benefits**
- Polypropylene cable ties provide excellent resistance to chemicals and salts.
  - Inside serrations allow for strong hold on cables and wire bundles.
  - Head design provides high tensile strength with very low insertion force.
  - Bent tail ensures a quick and simple installation.

**Product Description** HellermannTyton high temperature cable ties are made of specially formulated materials providing various levels of temperature resistance and performance. The cable ties feature inside serrations providing a positive hold onto wire and cable bundles. The head design guarantees high tensile strength, as well as a low insertion force. The bent tail design allows quick and simple installations by hand. For high volume applications, tensioning tools are available to ensure consistent and safe installation.

**Fixation Method (FF)** None

**Identification Plate Position** none

**Releasable Closure (Yes/No)** No

**Tie Closure** plastic pawl

**Variant** Inside Serrated

**Short Description** High Temp Tie, 8" Long, 25lb Tensile Strength, PP, Black, 100/pkg

### Product Dimensions

**Minimum Tensile Strength (imperial)** 25.0 lbs

**Minimum Tensile Strength (N)** 111.0 N

**Length L (imperial)** 8.0 "

**Length L (metric)** 202.0 mm

**Width W (imperial)** 0.19 "

**Width W (metric)** 4.8 mm

**Bundle Diameter min (imperial)** 0.5 "

**Bundle Diameter min (metric)** 12.7 mm

**Bundle Diameter max (imperial)** 1.75 "

**Bundle Diameter max (metric)** 44.5 mm

**Thickness T (imperial)** 0.05 "

**Thickness T (Metric)** 1.2 mm

### Logistics and Packaging

**Quantity per** bag

**Package Quantity** 100

Carton Quantity 5000

## Material and Specifications

---

<b>Material</b>	Polypropylene (PP)
<b>Material Shortcut</b>	PP
<b>Flammability</b>	UL94 HB
<b>Halogenfree</b>	Yes
<b>Operating Temperature</b>	-40 °F to +239 °F (-40 °C to +115 °C)
<b>ROHS Conformity</b>	Yes
<b>UL Listed (US and Canada)</b>	No
<b>UL Recognized (US and Canada)</b>	No